



TELECOM REGULATORY AUTHORITY OF INDIA

Independent Drive Test Report

Madhya Pradesh LSA

September 2025

Contents

1. Introduction	3
2. Executive Summary (LSA)	3
2.1 Drive test details	3
2.2 Drive test routes	4
2.3 Summary of areas covered	4
2.4 Telecom service providers detected frequency bands	5
2.5 Performance against key QoS parameters	5
3. QoS performance analysis-LSA level	6
3.1 Overview	7
3.2 Voice performance	7
3.3 Data performance	10
4. Detailed QoS performance analysis	12
4.1 Overview	12
4.2 City	12
4.2.1 Drive test route	12
4.2.2 Areas covered	12
4.2.3 Voice performance	12
4.2.4 Data performance	21
4.3 Hotspots	22
4.3.1 Locations	22
4.3.2 Hotspot covered	22
4.3.3 Voice performance	23
4.3.4 Data performance (Auto-selection mode 5G/4G/3G/2G)	25
4.3.5 Data performance (5G Only & 4G Only Download & Upload Speed)	30
4.4 Walk Test	33
4.4.1 Walk test locations	33
4.4.2 Walk Test Covered	33
4.4.3 Voice Performance	33
4.4.4 Data Performance	34
4.5 Railway	36
4.5.1 Drive test route	36
4.5.2 Routes Covered	36
4.5.3 Voice performance	36
4.5.4 Data performance	40

5. Voice & Data Key findings	42
5.1 Overall Voice.....	42
5.2 Overall Data	42
5.3 Operator wise Key Findings.....	43
6. Annexure	47
6.1 Route wise coverage map	47
6.1.1 City	47
6.1.2 Railway	50
7. Appendix	53
7.1 Appendix-I	53
7.1.1 Drive test setup	53
7.1.2 Drive test Methodology	55
7.2 Appendix-II	57
7.2.1 Network Performance Parameters for Voice calls	57
7.2.2 Network Performance Parameters Data tests	58

1. Introduction

TRAI Act, 1997 mandates the Authority to ensure the services delivered through various telecommunications networks meet the required quality standards prescribed, to protect the interest of the consumers of telecommunication services. TRAI is also responsible for conducting the periodical audit of such services provided by the service providers so as to protect the interests of the consumers of telecommunications services.

Accordingly, TRAI has engaged M/s RedMango Analytics Pvt. Ltd. to undertake assessment of Quality of Service of mobile service through Independent Drive Test (IDT).

In IDT, the performance of all service providers providing service in a Licensed Service Area (LSA) through various technologies (like 2G/ 3G/ 4G/ 5G) for voice and data are measured by conducting drive test. The drive test routes are finalised based on various objective criteria like reported network performance, consumer complaints etc. Methodology adopted for conducting IDT is elaborated in **APPENDIX-I**.

2. Executive Summary (LSA)

2.1 Drive test details

This report covers the findings of the IDT undertaken in Madhya Pradesh License Service Area (LSA) during the month of September-2025 under the supervision of TRAI Regional Office (RO) Bhopal. Details of route / area covered during the IDT are as given below:

S. No	Drive test route	Type of route	Distance covered (KMs)	From date	To date
1	Gwalior	City	370.2	01-Sep-2025	03-Sep-2025
2	Gwalior	Inter Operator Calling	21.4	03-Sep-2025	03-Sep-2025
3	Gwalior	Hotspot	12 Locations	01-Sep-2025	04-Sep-2025
4	Gwalior	Walk test	4.7	04-Sep-2025	04-Sep-2025
5	Itarsi to Burhanpur	Railway	252.2	18-Sep-2025	18-Sep-2025

Table-1: Drive test summary

2.2 Drive test routes

The map provides overview of drive test routes indicating city drive, Inter-operator call test, hotspots, walk test and railway as per the legends shown on the map.




Figure-1: Drive test routes

2.3 Summary of areas covered

a) City-Nearby Malanpur, Tilori, Narayan Vihar, Jinawali, Bhaypura, Anand Nagar, Garam Sadak, Lashkar, Mahalgaon, Kampoo, Jhansi Road, Rairu- Dabra Bypass Road etc.

b) Hotspot

1. Captain Roop Singh Cricket Stadium
2. DB Mall
3. Dindayal City Mall
4. Gwalior Fort
5. Gwalior Interstate Bus Stand
6. Gwalior Railway Station
7. Jaya Arogya Hospital
8. Maharaj Bada Gwalior
9. Malanpur Chauraha
10. Rajmata Vijayaraje Scindia Airport
11. RVSKVV Gwalior Rajmata Vijayaraje Scindia Medical University
12. Tomb of Tansen

c) Walk test

1. Gandhi Zoological Park Zoo Gwalior
2. Gwalior Railway Station
3. Rajmata Vijayaraje Scindia Airport

d) Railway

1. Itarsi to Burhanpur

2.4 Telecom service providers detected frequency bands


Technologies covered during the IDT and frequency bands in use are summarised in table below:

S.no.	Name of TSP	Technology	Frequency Bands (In MHz)
1	Bharti Airtel Ltd.	2G	1800
2	Bharti Airtel Ltd.	4G	850,1800,2100,2300
3	Bharti Airtel Ltd.	5G	3500
4	BSNL	2G	900
5	BSNL	3G	2100
6	BSNL	4G	700,2100,2500
7	Reliance JIO Infocomm Ltd.	4G	850,1800,2300
8	Reliance JIO Infocomm Ltd.	5G	700,3500
9	Vodafone Idea Ltd.	2G	900
10	Vodafone Idea Ltd.	4G	900,1800,2300,2500

Table-2: Telecom service provider (TSP) covered in IDT

2.5 Performance against key QoS parameters

CSSR: Call Setup Success Rate (in %), **CST:** Call Setup Time (in seconds), **DCR:** Drop Call Rate (in %) & **MOS:** Mean Opinion Score.



Summary-Voice services

Call Setup Success Rate: Airtel, BSNL, RJIL and VIL have 99.66%, 81.33%, 99.44% and 98.22% call setup success rate respectively in Auto-selection mode (5G/4G/3G/2G).

Call Setup Time: Airtel, BSNL, RJIL & VIL have call setup time of 1.28, 2.17, 0.64 and 0.80 seconds respectively in Auto-selection mode (5G/4G/3G/2G).

Drop Call Rate: Airtel, BSNL, RJIL and VIL have drop call rate of 0.11%, 7.81%, 0.11% and 0.23% respectively in Auto-selection mode (5G/4G/3G/2G).

Call Silence/Mute Rate: Airtel, BSNL, RJIL and VIL have silence call rate of 0.16%, 3.04%, 0.48% and 0.47% respectively in packet switched network (4G/5G).

Mean Opinion Score (MOS): Airtel, BSNL, RJIL and VIL have average MOS of 4.01, 3.18, 3.91 and 3.99 respectively.

Summary-Data services

Data Download performance (Overall): Average download speed of Airtel (5G/4G/2G) is 119.58 Mbps, BSNL (4G/3G/2G) is 1.45 Mbps, RJIL (5G/4G) is 227.27 Mbps and VIL (4G/2G) is 24.40 Mbps.

Data Upload performance (Overall): Average upload speed of Airtel (5G/4G/2G) is 24.77 Mbps, BSNL (4G/3G/2G) is 3.13 Mbps, RJIL (5G/4G) is 26.04 Mbps and VIL (4G/2G) is 9.49 Mbps.

Latency (Overall): Airtel, BSNL, RJIL & VIL 50th percentile latency is 34.40 ms, 87.50 ms, 22.10 ms & 30.45 ms respectively.

Data performance - Hotspots (in Mbps):

Airtel - 4G D/L: 46.97 4G U/L: 6.65
 5G D/L: 153.09 5G U/L: 41.13
 BSNL- 4G D/L: 1.82 4G U/L: 4.14
 RJIL- 4G D/L: 39.86 4G U/L: 10.85
 5G D/L: 149.95 5G U/L: 13.57
 VIL- 4G D/L: 27.87 4G U/L: 10.99

Note- "D/L" Download speed, "U/L" Upload speed

QoS Performance Analysis- Madhya Pradesh LSA

3. QoS performance analysis-LSA level

3.1 Overview

This section provides summary of overall QoS performance of the telecom service provider's network in the LSA by aggregating the results of drive tests conducted in the Madhya Pradesh LSA during the month of September-2025 covering city drive, hotspots, walk test and Railway. (Refer Table 1)

3.2 Voice performance

(a) Voice Call Performance in 3G/2G network mode only: 3G/2G network mode testing has been done to reflect experience for respective users as they have only 3G/2G compatible handsets.

Parameters	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
Call Attempts	619	623	621
Call Setup Success Rate %	99.84	97.75	99.52
Drop Call Rate %	0.00	1.15	0.00
Call Setup Time-Average (Second)	4.46	4.11	3.07
Handover Success Rate %	98.62	99.39	99.54

Table-3: Summary of voice call performance in 3G/2G network mode only.




Figure-2: Call setup success rate and drop call rate performance.

Number of unique cell Id's covered in Voice test- Technology wise			
Technology	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
3G	NA	236	NA
2G	598	58	552

Table-4: Technology wise number of network cell Id's latched during drive test.

Note-

- RJIL does not have 3G/2G network.
- NA- Service provider doesn't provide services in respective technology.

(b) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	887	1039	893	898
Call Setup Success Rate %	99.66	81.33	99.44	98.22
Drop Call Rate %	0.11	7.81	0.11	0.23
Call Setup Time-Average (Second)	1.28	2.17	0.64	0.80
Handover Success Rate %	99.84	97.21	99.91	99.81

Table-5: Summary of voice call performance in network auto-selection mode.




Figure-3: Performance for call setup success rate and drop call rate.

Parameter	Service Provider			
	Mobile-to-Mobile (5G/4G - Open Mode)			
	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider Network)	627	592	620	638
Number of silence call for >4 Sec	1	18	3	3
Silence Call Rate %	0.16	3.04	0.48	0.47
Number of silence instances for >4 Sec	2	21	3	3
Number of silence instances for >3 Sec	3	34	4	16
Number of silence instances for >2 sec	20	58	19	44
RTP Jitter (4G & 5G) in ms	4.54	5.18	7.62	9.14
Packet loss Rate Downlink %	0.36	4.04	0.27	1.30
Packet loss Rate Uplink %	0.48	3.20	0.37	1.06

Table-6: Summary of silence instances & packet loss rate for mobile to mobile calls.

Number of unique cell Id's covered in Voice test- Technology wise				
Technology	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
5G	0	NA	618	NA
4G	1389	561	2020	1504
3G	NA	36	NA	NA
2G	1	75	NA	28

Table-7: Technology wise number of network cell Id's latched during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.
- 0- No cell Id's were found in respective technology.

(c) Mean Opinion Score (MOS) performance for speech quality:

Mean opinion score indicates quality of speech observed during the drive test across different technologies. This parameter has been calculated for mobile-to-mobile calls made within same operator network in auto mode (5G/4G/3G/2G). As per ITU-T Recommendation P.863.1, MOS values means: 5-Excellent, 4-Good, 3-Fair, 2-Poor, 1-Bad.

Speech Quality (MOS) distribution	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
Total Number of MOS Samples for calls table-6	3643	2892	3603	3639
Speech Quality (Average MOS)	4.01	3.18	3.91	3.99
Number of samples with MOS ≥ 4 to < 5 (Excellent)	3098	895	2586	2736
Number of samples with MOS ≥ 3 to < 4 (Good)	433	859	824	664
Number of samples with MOS ≥ 2 to < 3 (Fair)	75	796	155	124
Number of samples with MOS ≥ 1 to < 2 (Poor)	37	342	38	115
%age of samples with MOS ≥ 4 to < 5 (Excellent)	85.04%	30.95%	71.77%	75.19%
%age of samples with MOS ≥ 3 to < 4 (Good)	11.89%	29.70%	22.87%	18.25%
%age of samples with MOS ≥ 2 to < 3 (Fair)	2.06%	27.52%	4.30%	3.41%
%age of samples with MOS ≥ 1 to < 2 (Poor)	1.02%	11.83%	1.05%	3.16%

Table-8: Summary of speech quality (MOS) samples.




Figure- 4: Distribution of samples in MOS range.

(d) Inter-service provider voice call performance: To check the performance of inter-service providers call setup success rate, total 70 to 85 inter operator calls were attempted. The call setup success rate and call setup time observation is as below.

Call Setup Success Rate %				
From Service Provider	To Service Provider			
	AIRTEL	BSNL	RJIL	VIL
AIRTEL	NA	98.70	100.00	100.00
BSNL	96.20	NA	100.00	82.86
RJIL	100.00	100.00	NA	100.00
VIL	98.75	100.00	98.78	NA

Table-9: Call setup success rate across service providers

Note-

- NA- Only inter-operator calls were measured during test.

Call setup time average (seconds)				
From Service Provider	To Service Provider			
	AIRTEL	BSNL	RJIL	VIL
AIRTEL	NA	2.22	2.07	2.64
BSNL	3.14	NA	3.22	2.86
RJIL	1.92	2.12	NA	2.12
VIL	2.12	3.32	2.59	NA

Table-10: Call setup time across service providers.

Note-

- NA- Only inter-operator calls were measured during test.

3.3 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbits/s)	Average	119.58	1.45	227.27	24.40
	80th Percentile	218.12	2.03	410.10	42.00
	20th Percentile	16.28	0.52	26.57	6.19
Upload Throughput (Mbits/s)	Average	24.77	3.13	26.04	9.49
	80th Percentile	47.83	4.39	50.11	17.27
	20th Percentile	3.66	1.39	3.68	2.12
Latency (ms)	50th Percentile	34.40	87.50	22.10	30.45

Table-11: Summary of data performance in network auto-selection mode.




Figure- 5: Download and Upload throughput.

Number of unique cell Id's covered in Data test- Technology wise				
Technology	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
5G	0	NA	1002	NA
4G	1415	573	343	1566
3G	NA	69	NA	NA
2G	6	55	NA	4

Table-12: Technology wise number of network cell Id's latched during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.
- 0- No cell Id's were found in respective technology.

Detailed QoS Performance Analysis

Parameters	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
Call Attempts	619	623	621
Call Setup Success Rate %	99.84	97.75	99.52
Drop Call Rate %	0.00	1.15	0.00
Call Setup Time-Average (Second)	4.46	4.11	3.07
Handover Success Rate %	98.62	99.39	99.54

Table-13: Summary of voice call performance in 3G/2G network mode only.




Figure-7: Performance for call setup success rate.




Figure-8: Performance for drop call rate.

(b) Network Technology: This section represent time spent on various network technologies.

Technology	Service Provider		
	AIRTEL	BSNL	VIL
3G	NA	90.03%	NA
2G	99.98%	9.74%	99.95%
Limited Service	0.02%	0.23%	0.05%

Table-14: Time spent on technology during drive test 3G/2G network mode.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-9: Serving technology plots 3G/2G network mode – AIRTEL




Figure-10: Serving technology plots 3G/2G network mode –BSNL.




Figure-11: Serving technology plots 3G/2G network mode –VIL.

(c) Network Signal Strength Distribution: The following chart represents signal strength distribution for 3G/2G network mode only. (Refer figure- 35, 36 & 37 for map view)




Figure-12: Signal strength distribution 3G/2G network mode only.

Observations:

- Airtel has 26% of samples falling in the excellent signal strength category.
- BSNL has 17% of samples falling in the excellent signal strength category.
- VIL has 35% of samples falling in the excellent signal strength category.

(d) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	642	731	643	650
Call Setup Success Rate %	100.00	84.40	99.84	98.46
Drop Call Rate %	0.00	8.91	0.00	0.16
Call Setup Time Average (Second)	1.22	2.20	0.63	0.81
Handover Success Rate %	99.89	97.81	99.92	99.80

Table-15: Summary of voice call performance in network auto-selection mode.




Figure-13: Performance for call setup success rate.




Figure-14: Performance for drop call rate.

Parameter	Service Provider			
	Mobile-to-Mobile (5G/4G - Open Mode)			
	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider Network)	627	592	620	638
Number of silence call for >4 Sec	1	18	3	3
Silence Call Rate %	0.16	3.04	0.48	0.47
Number of silence instances for >4 Sec	2	21	3	3
Number of silence instances for >3 Sec	3	34	4	16
Number of silence instances for >2 sec	20	58	19	44
RTP Jitter (4G & 5G) in ms	4.54	5.18	7.62	9.14
Packet loss Rate Downlink %	0.36	4.04	0.27	1.3
Packet loss Rate Uplink %	0.48	3.20	0.37	1.06

Table-16: Summary of silence instances & packet loss rate for mobile to mobile call.

(e) Mean Opinion Score (MOS) performance for speech quality:

Mean opinion score indicate quality of speech observed during the drive test across different technologies. This parameter has been calculated for mobile to mobile calls made within same operator network in auto mode (5G/4G/3G/2G). As per ITU-T Recommendation P.863.1, MOS value means: 5-Excellent, 4-Good, 3-Fair, 2-Poor, 1-Bad.

Speech Quality (MOS) distribution	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
Total Number of MOS Samples for calls in table-16	3643	2892	3603	3639
Speech Quality (Average MOS)	4.01	3.18	3.91	3.99
Number of samples with MOS ≥ 4 to <5 (Excellent)	3098	895	2586	2736
Number of samples with MOS ≥ 3 to <4 (Good)	433	859	824	664
Number of samples with MOS ≥ 2 to <3 (Fair)	75	796	155	124
Number of samples with MOS ≥ 1 to <2 (Poor)	37	342	38	115
%age of samples with MOS ≥ 4 to <5 (Excellent)	85.04%	30.95%	71.77%	75.19%
%age of samples with MOS ≥ 3 to <4 (Good)	11.89%	29.70%	22.87%	18.25%
%age of samples with MOS ≥ 2 to <3 (Fair)	2.06%	27.52%	4.30%	3.41%
%age of samples with MOS ≥ 1 to <2 (Poor)	1.02%	11.83%	1.05%	3.16%

Table-17: Summary of speech quality (MOS) samples.




Figure-15: Distribution of samples in MOS range.

(f) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	10.08%	NA	16.56%	NA
4G	89.92%	87.83%	83.44%	99.22%
3G	NA	4.77%	NA	NA
2G	0.00%	6.03%	NA	0.72%
Limited Service	0.00%	1.36%	0.00%	0.06%

Table-18: Time spent on technology during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-16: Serving technology plots in auto-selection mode (5G/4G/3G/2G) -AIRTEL.




Figure-17: Serving technology plots in auto-selection mode (5G/4G/3G/2G) -BSNL.




Figure-18: Serving technology plots in auto-selection mode (5G/4G/3G/2G)- RJIL.




Figure-19: Serving technology plots in auto-selection mode (5G/4G/3G/2G) – VIL

(g) Network Signal Strength Distribution: The following chart provide signal strength distribution for auto-selection mode (5G/4G/3G/2G). (Refer figure-38, 39, 40 & 41 for map view)




Figure-20: Signal strength distribution auto-selection mode 5G/4G/3G/2G.

Observations:

- Airtel has 29% of samples falling in the excellent signal strength category.
- BSNL has 14% of samples falling in the excellent signal strength category.
- RJIL has 45% of samples falling in the excellent signal strength category.
- VIL has 30% of samples falling in the excellent signal strength category.

4.2.4 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbits/s)	Average	134.95	1.48	261.62	23.98
	80th Percentile	230.91	1.89	456.85	41.21
	20th Percentile	26.80	0.52	63.73	6.12
Upload Throughput (Mbits/s)	Average	27.21	3.09	29.89	9.92
	80th Percentile	50.92	4.37	55.96	18.47
	20th Percentile	4.91	1.34	4.56	2.05
Latency (ms)	50th Percentile	33.45	88.50	20.40	29.70

Table-19: Summary of Data performance in network auto-selection mode.




Figure- 21: Download throughput




Figure- 22: Upload throughput

4.3 Hotspots

Hotspot testing has been done from 1st September to 4th September 2025. Twelve locations have been tested in the city.

4.3.1 Locations




Figure- 23: Hotspot locations

4.3.2 Hotspot covered

1. Captain Roop Singh Cricket Stadium
2. DB Mall
3. Dindayal City Mall
4. Gwalior Fort
5. Gwalior Interstate Bus Stand
6. Gwalior Railway Station
7. Jaya Arogya Hospital
8. Maharaj Bada Gwalior
9. Malanpur Chauraha
10. Rajmata Vijayaraje Scindia Airport
11. RVSKVV Gwalior Rajmata Vijayaraje Scindia Medical University
12. Tomb of Tansen

4.3.3 Voice performance

Overall Voice Performance				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	120	120	120	120
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.23	1.59	0.58	0.69

Table-20: Overall summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Captain Roop Singh Cricket Stadium				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.21	1.19	0.53	0.55

Table-21: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

DB Mall				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.26	1.24	0.54	0.76

Table-22: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Dindayal City Mall				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.23	1.17	0.61	0.80

Table-23: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Gwalior Interstate Bus Stand				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.23	1.33	0.64	0.69

Table-24: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Gwalior Fort				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.20	4.57	0.56	0.60

Table-25: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Gwalior Railway Station				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.22	1.12	0.81	0.74

Table-26: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Jaya Arogya Hospital				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.22	1.99	0.54	0.59

Table-27: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Maharaj Bada Gwalior				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.26	1.25	0.62	0.78

Table-28: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Malanpur Chauraha				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.22	1.22	0.51	0.89

Table-29: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Rajmata Vijayaraje Scindia Airport				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.20	1.71	0.50	0.60

Table-30: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

RVSKVV Gwalior Rajmata Vijayaraje Scindia Medical University				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.25	1.20	0.61	0.60

Table-31: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Tomb of Tansen				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.21	1.22	0.55	0.64

Table-32: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

4.3.4 Data performance (Auto-selection mode 5G/4G/3G/2G)

Overall Data Performance				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	143.16	1.74	152.25	28.24
Download Throughput 80th Percentile (Mbit/s)	230.76	2.28	289.45	53.71
Download Throughput 20th Percentile (Mbit/s)	65.88	1.08	6.39	9.40
Download Session Setup Success Rate %	100.00	88.33	100.00	96.67
Upload Throughput Average (Mbits/s)	32.96	3.50	20.06	8.96
Upload Throughput 80th Percentile (Mbit/s)	53.51	4.43	32.62	19.62
Upload Throughput 20th Percentile (Mbit/s)	10.77	2.49	2.83	1.72
Upload Session Setup Success Rate %	100.00	88.33	100.00	96.67
Web Browsing Delay (Second)	4.43	5.15	4.66	5.01
Youtube Initial Buffer Delay (Second)	0.97	1.53	1.18	1.14
Latency (ms) - 50th Percentile	34.15	151.00	23.65	31.00
Jitter (ms)	6.41	174.92	34.10	51.24
Packet Loss Rate%	3.39	99.86	3.23	20.96
Packet Loss Rate- 90th percentile	8.43	100.00	7.84	91.01

Table-33: Overall Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Captain Roop Singh Cricket Stadium				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	115.59	1.19	360.96	11.87
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	27.16	3.21	18.16	16.81
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	5.09	8.06	4.50	6.55
Youtube Initial Buffer Delay (Second)	0.95	1.10	0.70	0.99
Latency (ms) - 50th Percentile	33.68	-	25.25	28.63
Jitter (ms)	2.16	-	5.58	49.59
Packet Loss Rate%	0.00	100.00	0.00	1.70

Table-34: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.				
DB Mall				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	68.65	1.66	4.83	13.39
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	12.50	4.56	31.58	1.43
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	2.62	2.78	2.43	2.61
Youtube Initial Buffer Delay (Second)	0.99	1.76	0.96	1.30
Latency (ms) - 50th Percentile	54.00	-	25.00	34.90
Jitter (ms)	8.74	-	3.77	47.48
Packet Loss Rate%	0.00	100.00	7.00	5.10

Table-35: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.				
Dindayal City Mall				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	206.03	2.59	184.55	8.41
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	61.34	5.47	12.02	2.64
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	4.90	6.90	4.96	6.00
Youtube Initial Buffer Delay (Second)	0.71	0.98	0.79	0.92
Latency (ms) – 50 th Percentile	47.45	-	28.65	29.50
Jitter (ms)	3.16	-	20.30	35.09
Packet Loss Rate%	0.10	100.00	0.30	3.40

Table-36: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.				
--	--	--	--	--

Gwalior Interstate Bus Stand				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	89.17	3.84	6.77	67.15
Download Session Setup Success Rate %	100.00	100.00	100.00	60.00
Upload Throughput Average (Mbits/s)	36.99	2.63	2.65	25.49
Upload Session Setup Success Rate %	100.00	100.00	100.00	60.00
Web Browsing Delay (Second)	2.22	2.84	4.27	4.08
Youtube Initial Buffer Delay (Second)	0.70	1.40	0.98	0.67
Latency (ms) - 50th Percentile	31.60	56.50	20.63	764.75
Jitter (ms)	2.87	70.18	17.24	393.74
Packet Loss Rate%	0.00	98.50	7.90	96.50

Table-37: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Gwalior Fort				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	147.13	-	22.23	50.45
Download Session Setup Success Rate%	100.00	0.00	100.00	100.00
Upload Throughput Average (Mbits/s)	12.22	-	2.97	19.79
Upload Session Setup Success Rate %	100.00	0.00	100.00	100.00
Web Browsing Delay (Second)	5.66	-	7.08	5.07
Youtube Initial Buffer Delay (Second)	1.90	-	0.91	0.72
Latency (ms)- 50th Percentile	71.25	174.75	22.90	28.00
Jitter (ms)	22.31	193.87	297.41	8.32
Packet Loss Rate%	29.80	99.80	15.00	0.40

Table-38: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Download, Upload, Web browsing and Youtube tests were failed.

Gwalior Railway Station				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	50.50	1.35	5.47	3.22
Download Session Setup Success Rate%	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	17.63	3.71	3.63	1.66
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	2.64	3.17	2.66	2.82
Youtube Initial Buffer Delay (Second)	0.83	3.05	1.62	2.45
Latency (ms)- 50th Percentile	62.00	-	31.60	49.30
Jitter (ms)	12.88	-	7.87	138.82
Packet Loss Rate%	9.20	100.00	7.30	41.60

Table-39: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.

Jaya Arogya Hospital				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	91.98	2.37	164.98	14.53
Download Session Setup Success Rate%	100.00	80.00	100.00	100.00
Upload Throughput Average (Mbits/s)	4.89	3.92	9.88	7.00
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	6.11	7.18	4.43	6.18
Youtube Initial Buffer Delay (Second)	1.43	0.97	0.98	0.83
Latency (ms)- 50th Percentile	19.90	-	21.80	-
Jitter (ms)	7.79	-	5.84	-
Packet Loss Rate%	0.10	100.00	0.00	100.00

Table-40: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.				
Maharaj Bada Gwalior				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	277.49	1.64	279.83	17.54
Download Session Setup Success Rate%	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	49.98	3.51	71.98	20.88
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	2.30	2.67	2.43	3.10
Youtube Initial Buffer Delay (Second)	0.91	1.32	0.82	0.75
Latency (ms)- 50th Percentile	39.80	-	19.00	30.75
Jitter (ms)	2.73	-	8.10	16.61
Packet Loss Rate%	0.00	100.00	0.10	0.70

Table-41: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.				
Malanpur Chauraha				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	240.49	1.00	47.93	48.23
Download Session Setup Success Rate%	100.00	80.00	100.00	100.00
Upload Throughput Average (Mbits/s)	68.99	2.50	3.86	4.30
Upload Session Setup Success Rate %	100.00	80.00	100.00	100.00
Web Browsing Delay (Second)	2.41	2.88	2.61	2.33
Youtube Initial Buffer Delay (Second)	0.97	1.88	2.09	0.87
Latency (ms)- 50th Percentile	21.15	-	25.43	29.00
Jitter (ms)	4.96	-	8.16	7.57
Packet Loss Rate%	0.00	100.00	0.10	0.40

Table-42: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.				
--	--	--	--	--

Rajmata Vijayaraje Scindia Airport				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	245.43	1.00	221.51	51.88
Download Session Setup Success Rate%	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	39.94	2.39	7.39	3.52
Upload Session Setup Success Rate %	100.00	80.00	100.00	100.00
Web Browsing Delay (Second)	4.72	4.41	6.55	6.09
Youtube Initial Buffer Delay (Second)	0.74	2.00	0.77	0.85
Latency (ms)- 50th Percentile	30.30	-	16.30	31.50
Jitter (ms)	1.79	-	19.65	31.34
Packet Loss Rate%	0.00	100.00	0.60	0.70

Table-43: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.

RVSKVV Gwalior Rajmata Vijayaraje Scindia Medical University				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	56.22	1.03	149.29	18.65
Download Session Setup Success Rate%	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	10.41	3.34	2.46	3.40
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	5.66	6.65	7.09	7.09
Youtube Initial Buffer Delay (Second)	0.95	1.06	6.13	2.29
Latency (ms)- 50th Percentile	22.08	-	18.80	34.60
Jitter (ms)	5.26	-	8.15	13.03
Packet Loss Rate%	1.50	100.00	0.50	0.60

Table-44: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.

Tomb of Tansen				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	129.29	1.43	378.66	49.08
Download Session Setup Success Rate%	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	53.51	2.85	74.15	7.17
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	5.60	5.39	5.01	5.42
Youtube Initial Buffer Delay (Second)	0.91	1.45	0.95	0.85
Latency (ms)- 50th Percentile	33.75	-	33.40	26.80
Jitter (ms)	2.22	-	5.89	15.58
Packet Loss Rate%	0.00	100.00	0.00	0.40

Table-45: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.

4.3.5 Data performance (5G Only & 4G Only Download & Upload Speed)

Overall Data Performance					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	153.09	-	149.95	-
	Upload Throughput Average (Mbits/s)	41.13	-	13.57	-
4G	Download Throughput Average (Mbits/s)	46.97	1.82	39.86	27.87
	Upload Throughput Average (Mbits/s)	6.65	4.14	10.85	10.99

Table-46: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
Captain Roop Singh Cricket Stadium					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	106.08	-	387.24	-
	Upload Throughput Average (Mbits/s)	27.86	-	18.09	-
4G	Download Throughput Average (Mbits/s)	36.14	1.05	90.34	22.13
	Upload Throughput Average (Mbits/s)	9.88	5.29	15.23	20.35

Table-47: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
DB Mall					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	40.85	-	6.24	-
	Upload Throughput Average (Mbits/s)	16.25	-	35.62	-
4G	Download Throughput Average (Mbits/s)	22.09	1.44	19.03	17.90
	Upload Throughput Average (Mbits/s)	1.39	3.59	13.95	1.53

Table-48: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
Dindayal City Mall					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	231.29	-	192.13	-
	Upload Throughput Average (Mbits/s)	59.89	-	10.56	-
4G	Download Throughput Average (Mbits/s)	50.80	3.93	58.61	6.57
	Upload Throughput Average (Mbits/s)	3.82	5.78	8.08	1.20

Table-49: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
Gwalior Interstate Bus Stand					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	73.50	-	7.94	-
	Upload Throughput Average (Mbits/s)	42.05	-	5.73	-
4G	Download Throughput Average (Mbits/s)	18.61	2.99	116.84	84.57
	Upload Throughput Average (Mbits/s)	4.71	4.95	24.09	34.64

Table-50: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
---	--	--	--	--	--

Gwalior Fort					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	108.10	-	11.42	-
	Upload Throughput Average (Mbits/s)	9.93	-	2.02	-
4G	Download Throughput Average (Mbits/s)	101.28	-	20.02	35.93
	Upload Throughput Average (Mbits/s)	10.46	-	2.28	17.02

Table-51: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
Gwalior Railway Station					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	45.14	-	6.45	-
	Upload Throughput Average (Mbits/s)	10.13	-	6.71	-
4G	Download Throughput Average (Mbits/s)	29.89	3.02	10.61	1.03
	Upload Throughput Average (Mbits/s)	4.90	6.26	6.87	11.16

Table-52: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
Jaya Arogya Hospital					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	132.72	-	202.70	-
	Upload Throughput Average (Mbits/s)	4.45	-	11.03	-
4G	Download Throughput Average (Mbits/s)	30.02	0.04	25.92	8.39
	Upload Throughput Average (Mbits/s)	1.60	2.02	3.11	1.88

Table-53: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
Maharaj Bada Gwalior					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	276.50	-	234.09	-
	Upload Throughput Average (Mbits/s)	65.80	-	26.26	-
4G	Download Throughput Average (Mbits/s)	67.65	3.35	23.83	15.70
	Upload Throughput Average (Mbits/s)	4.53	5.24	16.16	26.58

Table-54: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
Malanpur Chauraha					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	198.16	-	52.34	-
	Upload Throughput Average (Mbits/s)	65.27	-	4.40	-
4G	Download Throughput Average (Mbits/s)	71.99	1.30	0.05	40.84
	Upload Throughput Average (Mbits/s)	9.13	2.70	2.25	2.53

Table-55: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
---	--	--	--	--	--

Rajmata Vijayaraje Scindia Airport					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	310.17	-	260.34	-
	Upload Throughput Average (Mbits/s)	49.33	-	11.43	-
4G	Download Throughput Average (Mbits/s)	21.90	0.89	31.28	38.21
	Upload Throughput Average (Mbits/s)	7.04	2.86	6.08	3.18

Table-56: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
RVSKVV Gwalior Rajmata Vijayaraje Scindia Medical University					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	54.27	-	61.69	-
	Upload Throughput Average (Mbits/s)	11.85	-	5.35	-
4G	Download Throughput Average (Mbits/s)	43.17	1.01	36.02	20.04
	Upload Throughput Average (Mbits/s)	4.63	2.90	20.24	5.62

Table-57: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
Tomb of Tansen					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	115.22	-	376.77	-
	Upload Throughput Average (Mbits/s)	59.86	-	25.62	-
4G	Download Throughput Average (Mbits/s)	70.17	1.00	45.74	43.11
	Upload Throughput Average (Mbits/s)	17.76	3.20	11.86	6.21

Table-58: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "--Respective technology was not observed during the test.					
---	--	--	--	--	--

4.4 Walk Test

Walk Test has been conducted on 4th September 2025. Three locations have been tested in the city.

4.4.1 Walk test locations




Figure-24: Walk Test locations.

4.4.2 Walk Test Covered

1. Gandhi Zoological Park Zoo Gwalior
2. Gwalior Railway Station
3. Rajmata Vijayaraje Scindia Airport

4.4.3 Voice Performance

Gandhi Zoological Park Zoo Gwalior				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	17	18	18	18
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.24	1.36	0.57	0.86

Table-59: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Gwalior Railway Station				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	17	19	18	18
Call Setup Success Rate %	100.00	94.74	100.00	100.00
Drop Call Rate %	0.00	5.56	0.00	0.00
Call Setup Time-Average (Second)	1.25	1.21	0.52	0.79

Table-60: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Rajmata Vijayaraje Scindia Airport				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	22	25	23	22
Call Setup Success Rate %	100.00	92.00	100.00	95.45
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	1.29	2.77	0.62	0.71

Table-61: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

4.4.4 Data Performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Gandhi Zoological Park Zoo Gwalior				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	62.96	2.56	314.68	12.31
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	9.68	7.02	14.57	2.87
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Latency (ms) - 50th Percentile	41.73	-	15.55	29.55

Table-62: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "--"Ping tests were failed.				
Gwalior Railway Station				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	76.73	2.46	17.24	28.83
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	42.28	5.06	19.89	8.59
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Latency (ms) - 50th Percentile	19.55	-	17.38	28.00

Table-63: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "--"Ping tests were failed.				
--	--	--	--	--

Rajmata Vijayaraje Scindia Airport				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	115.97	0.81	69.19	43.18
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	14.01	2.35	6.64	5.56
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Latency (ms) - 50th Percentile	33.98	-	36.95	28.00

Table-64: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "- "Ping tests were failed.

4.5 Railway

Drive test has been conducted on 18th September 2025 covering one Railway route. (Refer Table-1)

4.5.1 Drive test route




Figure-25: Drive test route railway.

4.5.2 Routes Covered

Itarsi to Burhanpur passing through Banapura, Timarni, Harda, Khirkiya, Chhanera, Khandwa and Neapanagar etc.

4.5.3 Voice performance

(a) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	69	126	71	70
Call Setup Success Rate %	95.65	38.89	94.37	92.86
Drop Call Rate %	1.52	20.41	1.49	1.54
Call Setup Time Average (Second)	1.99	3.59	0.94	0.95
Handover Success Rate %	99.69	91.89	99.80	99.87

Table-65: Summary of voice call performance in network auto-selection mode.




Figure-26: Performance for call setup success rate.




Figure-27: Performance for drop call rate.

(b) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	1.21%	NA	8.57%	NA
4G	97.32%	51.84%	90.00%	89.88%
3G	NA	10.73%	NA	NA
2G	0.11%	24.96%	NA	9.05%
Limited Service	1.35%	12.47%	1.42%	1.08%

Table-66: Time spent on technology during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-28: Serving technology plots in auto-selection mode (5G/4G/3G/2G)-AIRTEL.




Figure-29: Serving technology plots in auto-selection mode (5G/4G/3G/2G)-BSNL.




Figure-30: Serving technology plots in auto-selection mode (5G/4G/3G/2G)-RJIL.




Figure-31: Serving technology plots in auto-selection mode (5G/4G/3G/2G) -VIL

(c) Network Signal Strength Distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G). (Refer figure-42, 43, 44 & 45 for map view)




Figure-32: Signal strength distribution auto-selection mode 5G/4G/3G/2G.

Observations:

- Airtel has 7% of samples falling in the excellent signal strength category.
- BSNL has 12% of samples falling in the excellent signal strength category.
- RJIL has 17% of samples falling in the excellent signal strength category.
- VIL has 11% of samples falling in the excellent signal strength category.

4.5.4 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbits/s)	Average	34.77	0.60	115.27	22.00
	80th Percentile	51.12	0.96	185.95	38.33
	20th Percentile	1.13	0.26	5.45	3.65
Upload Throughput (Mbits/s)	Average	8.50	2.10	13.35	8.95
	80th Percentile	10.40	2.76	23.11	15.40
	20th Percentile	1.63	1.23	2.59	2.20
Latency (ms)	50th Percentile	44.30	73.00	23.10	32.90

Table-67: Summary of Data performance in network auto-selection mode.




Figure- 33: Download throughput




Figure- 34: Download throughput

5. Voice & Data Key findings

5.1 Overall Voice

1. Call Setup Success Rate:

- a) Airtel, BSNL and VIL have 99.84%, 97.75% and 99.52% call setup success rate respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL and VIL have 99.66%, 81.33%, 99.44% and 98.22% call setup success rate respectively in auto-selection mode (5G/4G/3G/2G). (refer table-5)
- c) None of the operator have 100.00% call setup success rate while calling on peer service provider's network for inter-operator calls except RJIL. (refer table-9)

2. Call Setup Time:

- a) Airtel, BSNL and VIL call setup time is 4.46, 4.11 & 3.07 seconds respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL & VIL call setup time is 1.28, 2.17, 0.64 & 0.80 seconds respectively in auto-selection mode (5G/4G/3G/2G). (refer table-5)

3. Call Silence/Mute Rate:

In packet switched network (4G/5G) BSNL, RJIL, VIL & Airtel have 3.04%, 0.48%, 0.47% & 0.16% silence call rate respectively. Further BSNL has higher RTP packet loss rate in downlink (4.04%) compared to VIL (1.30%), Airtel (0.36%) & RJIL (0.27%). In uplink the RTP packet loss rate is higher for BSNL (3.20%) compared to VIL (1.06%), Airtel (0.48%) and RJIL (0.37%). (refer table-6)

4. Drop Call Rate:

- a) Airtel, BSNL and VIL drop call rate is 0.00%, 1.15% and 0.00% respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL and VIL drop call rate is 0.11%, 7.81%, 0.11% and 0.23% respectively in auto-selection mode (5G/4G/3G/2G). (refer table-5)

5.2 Overall Data

1. Data download and upload performance (Overall i.e. LSA):

- a) Airtel, BSNL, RJIL and VIL average download speeds are 119.58 Mbps, 1.45 Mbps, 227.27 Mbps and 24.40 Mbps respectively. (refer table-11)
- b) Airtel, BSNL, RJIL and VIL average upload speeds are 24.77 Mbps, 3.13 Mbps, 26.04 Mbps and 9.49 Mbps respectively. (refer table-11)

2. Data download and upload performance (static i.e. while stationary):

- a) Airtel, BSNL, RJIL and VIL average download speeds are 143.16 Mbps, 1.74 Mbps, 152.25 Mbps and 28.24 Mbps respectively. (refer table-33)
- b) Airtel, BSNL, RJIL and VIL average upload speeds are 32.96 Mbps, 3.50 Mbps, 20.06 Mbps and 8.96 Mbps respectively. (refer table-33)

3. Data session setup success rate (static i.e. while stationary):

- a) Airtel, BSNL, RJIL and VIL have 100.00%, 88.33%, 100.00% and 96.67% download session setup success rate respectively. (refer table-33)
- b) Airtel, BSNL, RJIL and VIL have 100.00%, 88.33%, 100.00% and 96.67% upload session setup success rate respectively. (refer table-33)

5.3 Operator wise Key Findings

1. Airtel:

Voice

- 99.84% call setup success rate and 0.00% drop call rate have been observed in 3G/2G network mode for LSA/city drive. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-3 and 13)
- 99.66% call setup success rate and 0.11% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-5)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-15)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-20)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all walk test locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-59, 60 & 61)
- 95.65% call setup success rate and 1.52% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for railway drive. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-65)

Data

- Airtel has 119.58 Mbps average download speed & 24.77 Mbps average upload speed for LSA. (refer table-11)
- Airtel has 134.95 Mbps average download speed & 27.21 Mbps average upload speed across the measured routes for city drive. (refer table-19)
- DB Mall, Gwalior Interstate Bus Stand, Gwalior Railway Station, Jaya Arogya Hospital and RVSKVV Gwalior Rajmata Vijayaraje Scindia Medical University have less download speed (less than 100 Mbps) out of total 12 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table- 35, 37, 39, 40 & 44)
- DB Mall, Gwalior Fort, Gwalior Railway Station, Jaya Arogya Hospital and RVSKVV Gwalior Rajmata Vijayaraje Scindia Medical University have less upload speed (less than 20 Mbps) out of total 12 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table- 35, 38, 39, 40 & 44)
- Gandhi Zoological Park Zoo Gwalior and Gwalior Railway Station have less download speed (less than 100 Mbps) out of total 3 walk test locations for auto-selection mode (5G/4G/3G/2G). (refer table-62 & 63)
- Gandhi Zoological Park Zoo Gwalior and Rajmata Vijayaraje Scindia Airport have less upload speed (less than 20 Mbps) out of total 3 walk test locations for auto-selection mode (5G/4G/3G/2G). (refer table-62 & 64)
- Airtel has 34.77 Mbps average download speed & 8.50 Mbps average upload speed across the measured routes for railway drive. (refer table-67)

2. BSNL:

Voice

- 97.75% call setup success rate and 1.15% drop call rate have been observed in 3G/2G network mode for LSA/city drive. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-3 and 13)
- 81.33% call setup success rate and 7.81% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-5)
- 84.40% call setup success rate and 8.91% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-15)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-20)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at Gandhi Zoological Park Zoo Gwalior Walk test location. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-59)
- 94.74% call setup success rate and 5.56% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at Gwalior Railway Station Walk test location. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-60)
- 92.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at Rajmata Vijayaraje Scindia Airport Walk test location. Performance is not meeting the benchmark of 98.00% for call setup success rate (refer table-61)
- 38.89% call setup success rate and 20.41% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for railway drive. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-65)

Data

- BSNL has 1.45 Mbps average download speed & 3.13 Mbps average upload speed for LSA. (refer table-11)
- BSNL has 1.48 Mbps average download speed & 3.09 Mbps average upload speed across the measured routes for city drive. (refer table-19)
- All hotspot locations have less download speed (less than 10 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table- 34 to 45)
- All Walk test locations have less download speed (less than 10 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-62, 63 & 64)
- BSNL has 0.60 Mbps average download speed & 2.10 Mbps average upload speed across the measured routes for railway drive. (refer table-67)

3. RJIL:

Voice

- 99.44% call setup success rate and 0.11% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-5)
- 99.84% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-15)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-20)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all walk test locations Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-59, 60 & 61)
- 94.37% call setup success rate and 1.49% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for railway drive. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-65)

Data

- RJIL has 227.27 Mbps average download speed & 26.04 Mbps average upload speed for LSA. (refer table-11)
- RJIL has 261.62 Mbps average download speed & 29.89 Mbps average upload speed across the measured routes for city drive. (refer table-19)
- DB Mall, Gwalior Interstate Bus Stand, Gwalior Fort, Gwalior Railway Station and Malanpur Chauraha have less download speed (less than 100 Mbps) out of total 12 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-35, 37, 38, 39 & 42)
- All hotspot locations have less upload speed except DB Mall, Maharaj Bada Gwalior and Tomb of Tansen (less than 20 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-34, 36, 37, 38, 39, 40, 42, 43 & 44)
- Gwalior Railway Station and Rajmata Vijayaraje Scindia Airport have less download speed (less than 100 Mbps) out of total 3 walk test locations for auto-selection mode (5G/4G/3G/2G). (refer table-63 & 64)
- All Walk test locations have less upload speed (less than 20 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-62, 63 & 64)
- RJIL has 115.27 Mbps average download speed & 13.35 Mbps average upload speed across the measured routes for railway drive. (refer table-67)

4. VIL:

Voice

- 99.52% call setup success rate and 0.00% drop call rate have been observed in 3G/2G network mode for LSA/city drive. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-3 and 13)

- 98.22% call setup success rate and 0.23% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-5)
- 98.46% call setup success rate and 0.16% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-15)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-20)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at Gandhi Zoological Park Zoo Gwalior & Gwalior Railway Station Walk test locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-59 & 60)
- 95.45% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at Rajmata Vijayaraje Scindia Airport Walk test location. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-61)
- 92.86% call setup success rate and 1.54% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for railway drive. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-65)

Data

- VIL has 24.40 Mbps average download speed & 9.49 Mbps average upload speed for LSA. (refer table-11)
- VIL has 23.98 Mbps average download speed & 9.92 Mbps average upload speed across the measured routes for city drive. (refer table-19)
- Dindayal City Mall and Gwalior Railway Station have less download speed (less than 10 Mbps) out of total 12 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table- 36 & 39)
- DB Mall and Gwalior Railway Station have less upload speed (less than 2 Mbps) out of total 12 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-35 & 39)
- VIL has 22.00 Mbps average download speed & 8.95 Mbps average upload speed across the measured routes for railway drive. (refer table-67)

6. Annexure

6.1 Route wise coverage map

6.1.1 City




Figure-35: Signal strength 3G/2G network mode – AIRTEL.




Figure-36: Signal strength 3G/2G network mode – BSNL.




Figure-37: Signal strength 3G/2G network mode – VIL.




Figure-38: Signal strength auto-selection mode 5G/4G/3G/2G – AIRTEL.




Figure-39: Signal strength auto-selection mode 5G/4G/3G/2G – BSNL.




Figure-40: Signal strength auto-selection mode 5G/4G/3G/2G – RJIL.




Figure-41: Signal strength auto-selection mode 5G/4G/3G/2G – VIL.

6.1.2 Railway

i) Itarsi to Burhanpur




Figure-42: Signal strength auto-selection mode 5G/4G/3G/2G –AIRTEL




Figure-43: Signal strength auto-selection mode 5G/4G/3G/2G –BSNL




Figure-44: Signal strength auto-selection mode 5G/4G/3G/2G –RJIL.




Figure-45: Signal strength auto-selection mode 5G/4G/3G/2G –VIL

7. Appendix

The details of the setup used for conducting the drive test and the network or performance parameters captured under different conditions may be seen at Appendix-I. The calculation method of each QoS parameter is given in Appendix-II of the report. The summary of key equipment used in technical setup is as under

- **Device-1:** OnePlus Nord CE3 for 3G/2G CAT-15 Smartphone.
- **Device-2:** Samsung Galaxy S23 for 5G/4G/3G/2G CAT-20 Smartphone
- **Drive test Software:** Azenqos Engineering capable Applications to capture actual user experience.

7.1 Appendix-I

7.1.1 Drive test setup

Voice Call		
Call details	Technology	Detail
Call Setup Timeout	• 3G/2G auto mode- switch Call • 5G/4G/3G/2G auto mode- switch Call • 5G/4G MOS Call	30 Sec
Call Duration		90 Sec
Wait/ Guard Time		15 Sec

Table-68: Voice test detail

Note-

- There is 15 sec wait time after locking and before starting first call in 3G/2G call.
- 10 calls to be made at each Hotspot location.
- Minimum 10 Calls to be made during the walk test. Call count will be increased based on walk test distance.
- Speech quality (MOS) has been measured only in city drive & highway by making Mobile to Mobile call.
- 180 Sec calls were made only in highway & railway route drive.

Data Test		
Test Type	Technology	Detail
HTTP/FTP Download	5G/4G/3G/2G Auto Mode	500 MB File- 30 Sec Timeout, (Multithread 3- TCP Connection at a time)
HTTP/FTP Upload		250 MB File- 30 Sec Timeout, (Multithread 3- TCP Connection at a time)
YouTube Streaming		20 Sec Video & 25 sec Timeout (Only at Hotspot)
Web Browsing		3 popular websites (www.google.co.in , www.irctc.co.in , www.sbi.co.in) 20 sec timeout (only at Hotspot)

Latency		25 count- Dynamic 1000 count- Hotspot Payload- 42 bytes in all drive
---------	--	--

Table-69: Data test detail

Note-

- 5 Data iteration to be done at each hotspot location.
- Minimum 5 iteration to be made during the walk test. Iteration count will be increased based on walk test distance.
- Ping test to be performed only once at hotspot location.
- Youtube & Web browsing test to be performed at static location only.
- All values are taken up to two decimal places with round off.
- Download and upload testing has been done on FTP server for Airtel, BSNL & RJIL.
(Airtel, BSNL & RJIL not provided HTTP server)
- VIL download and upload testing is done on HTTP Server.




Figure-46: Number of handsets used in city & highway drive

MO: Mobile originating

MT: Mobile terminating




Figure-47: Number of handsets used in railway/metro/walktest/hotspot/coastal area

Note- 5G & 4G Lock mode testing has been performed at hotspot locations only.

7.1.2 Drive test Methodology

(a) Dynamic voice testing (on the move)




Figure-48: Voice test script for city/railway/metro/highway & coastal area

- 15 sec wait time is applied after locking Radio Access Technology (RAT) to 3G/2G and before starting first call in 3G/2G call.
- Speech quality (MOS) will be measured only City & Highway drive by making Mobile to Mobile calls.

(b) Hotspot voice testing



Figure-49: Voice test script for walktest/hotspot

- 10 calls to be made at each Hotspot location.
- Minimum 10 Calls to be made during the walk test. Call count will be increased based on walk test distance.

(c) Dynamic Data (internet) test




Figure-50: Data test script used in city/metro/railway/highway/walk test & coastal area

(d) Static Data(internet) testing




Figure-51: Data test script used at hotspot

- 5 Data iteration done at each hotspot location
- Min. 5 iteration made during the walk test.
- Web browsing duration mentioned above is for one web site only.
- Only 1 ping iteration (with 1000 Count) done at hotspot location.

7.2 Appendix-II

7.2.1 Network Performance Parameters for Voice calls

Parameter Name	Definition
Call Setup Success Rate	(i) Call Setup Success Rate is defined as the ratio of Established Calls to Call Attempts. 'Established Calls' mean the following events have happened in call setup: (a) Call attempt is made (b) The signaling channel is allocated (c) The call is routed to the outwards path of the terminating network (d) An alert signal is received by caller in the form of ring back tone, busy tone, or an announcement. CSSR = (Total Call Established/ Total Call Attempt) *100 As per QoS Regulation 2024 benchmark value is >=98%
Drop Call Rate	Call drop represents the service provider network's ability to maintain a call once it has been successfully established. This parameter shall include both incoming calls and outgoing calls which, once they have been established and have an assigned traffic channel/ bearer, are dropped, or interrupted before their normal completion by the user, the cause of the early termination being within the service provider's network Drop Call Rate = (Total Call Drop/Total Call Established) *100 As per QoS Regulation 2024 benchmark value is <=2%
Call Setup Time	Time taken from call initiate to call alerting/ringing. Call Setup Time = T2- T1 T2- Ringing (VoLTE/VoNR) & Alerting (for WCDMA & GSM), T1- Invite (VoLTE/VoNR) & CM Service Request (for WCDMA & GSM)
Voice Quality (MOS)	Voice quality in mobile networks is measured with algorithms based on ITU-T P.863 (POLQA). The grading for Voice quality has been given as: Excellent: MOS ≥ 4 and < 5 Good : MOS ≥ 3 and < 4 Fair : MOS ≥ 2 and < 3 Poor : MOS ≥ 1 and < 2
Handover Success Rate	Handover Success Rate = Count of successful handovers (All Technology Handover combined) / Total count of Handover Attempt (All Technology Handover combined) *100 Handover type which are considered- 2G Inter & Intra cell, 3G Soft & IRAT, 4G Inter & Intra frequency & SRVCC, 5G Inter & Intra frequency & 5G to 4G handovers.
Silence Call	A call which has ≥ 4 sec continuous RTP gap is considered as a Silence Call. Silence call rate = (count of silence call / Total calls established) *100 If a call observes multiple silence count ≥ 4 sec in a particular established call it has been taken as one silent event.

Jitter	The inter arrival jitter is the difference in the relative transit time for two packets. The relative transit time is the difference between a packet's Real-time Transport Protocol (RTP) timestamp and the receiver's clock at the time of arrival, measured in the same units. If S_i is the RTP timestamp from packet i, and R_i is the time of arrival in RTP timestamps units for packet i, then for two packets i and j the inter-arrival jitter D can be expressed as: $D(i,j) = (R_j - R_i) - (S_j - S_i)$ The interarrival jitter is calculated continuously as each data packet i is received from source $SSRC_n$, using this difference D for that packet and the previous packet $i-1$ in order of arrival (not necessarily in sequence), according to the formula $J(i) = J(i-1) + (D(i-1,i) - J(i-1))/16 \text{ or } 8$																																		
Downlink Packet Drop Rate	Number of RTP (Real-time Transport Protocol) Packets lost divided by total RTP packet received (against each source_SSRC and sequence number) at call originating handset. This KPI is calculated from MOS call for packet call only (VoNR/VoLTE)																																		
Uplink Packet Drop Rate	Number of RTP (Real-time Transport Protocol) Packets lost divided by total RTP packet received (against each source_SSRC and sequence number) at call terminating handset. This KPI is calculated from MOS call for packet call only (VoNR/VoLTE).																																		
Signal Strength	Signal strength is the signal power level received by the wireless user. <table><tr><th rowspan="2">Parameter Name</th><th rowspan="2">Technology</th><th colspan="4">Signal Strength (dBm)</th></tr><tr><th>Excellent</th><th>Good</th><th>Fair</th><th>Poor</th></tr><tr><td>Rx Level</td><td>GSM</td><td>0 to ≥ -65</td><td><-65 to ≥ -75</td><td><-75 to ≥ -85</td><td><-85 to min</td></tr><tr><td>RSCP</td><td>WCDMA</td><td>0 to ≥ -70</td><td><-70 to ≥ -80</td><td><-80 to ≥ -90</td><td><-90 to min</td></tr><tr><td>RSRP</td><td>LTE</td><td>0 to ≥ -80</td><td><-80 to ≥ -95</td><td><-95 to ≥ -110</td><td><-110 to min</td></tr><tr><td>SS_RSRP</td><td>NR</td><td>0 to ≥ -80</td><td><-80 to ≥ -95</td><td><-95 to ≥ -110</td><td><-110 to min</td></tr></table>	Parameter Name	Technology	Signal Strength (dBm)				Excellent	Good	Fair	Poor	Rx Level	GSM	0 to ≥ -65	<-65 to ≥ -75	<-75 to ≥ -85	<-85 to min	RSCP	WCDMA	0 to ≥ -70	<-70 to ≥ -80	<-80 to ≥ -90	<-90 to min	RSRP	LTE	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min	SS_RSRP	NR	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min
Parameter Name	Technology			Signal Strength (dBm)																															
		Excellent	Good	Fair	Poor																														
Rx Level	GSM	0 to ≥ -65	<-65 to ≥ -75	<-75 to ≥ -85	<-85 to min																														
RSCP	WCDMA	0 to ≥ -70	<-70 to ≥ -80	<-80 to ≥ -90	<-90 to min																														
RSRP	LTE	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min																														
SS_RSRP	NR	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min																														

Table-70: Network performance parameter and definition voice

7.2.2 Network Performance Parameters Data tests

Parameter Name	Definition
Download Speed (Mbps)	The download speed is defined as the data transmission rate that is achieved for downloading a test file from a test server to a test device. Download Speed = Total bytes transferred during download / Total time for transfer 80th percentile (upper range) & 20th percentile (lower range) value has been calculated for download throughput in dynamic drive and Hotspot combine data
Upload Speed (Mbps)	The upload speed is the data transmission rate that is achieved for uploading a test file from a test device to a test server. Upload Speed = Total bytes transferred during upload / Total time for transfer. 80th percentile (upper range) & 20th percentile (lower range) value has been calculated for upload throughput in dynamic drive and Hotspot combine data.
Download Session Setup Success Rate	(total download session established (successfully connected to server)/ total download session attempt) *100. This KPI has been calculated for Hotspot only.

Upload Session Setup Success Rate	(total upload session established (successfully connected to server)/ total upload session attempt)*100. This KPI need to report for Hotspot only.
Web Page Download Time	Web browsing test is used to measure performance in terms of opening a web/HTTP page. Time taken to open the web page successfully is considered as web browsing delay/web page download time.
Video Streaming Delay	The Video streaming delay is time taken from start of video transfer to First video frame displayed in player.
Latency	Latency is the time it takes for a small data set to be transmitted from a device to a server on the Internet and back to the same device again. The Latency is measured in milliseconds (ms). To calculate the one-way latency we just do half of the round-trip time. 50th percentile of one-way latency has been reported.
Jitter	Measure of variation in time in arrival of packets from a source to destination The consideration of packet delay jitter is considered by standard deviation of Inter Packet Delay Variation. If IPDV is used. By standard deviation is meant the average of standard deviation of IPDV on DL $IPDV(i) = D(i) - D(i-1)$ then Stdvs of IPDV is considered as jitter.
Packet Loss Rate	Number of packets lost out of total packet transferred during test. Packet loss rate = (Total packet lost / Total packet sent) *100 * Packet delay (using ping) >90 ms considered as packet loss and included in packet loss rate. * Packet loss rate is calculated based on ICMP *90th percentile for Packet loss rate has been reported in overall Hotspot performance summary.

Table-71: Network performance parameter and definition Data

Disclaimer: The observations presented above and, in the reports, represent the performance of the service providers on the area/route under test on the day/time of conducting the drive test and no inference whatsoever may be drawn regarding the quality of the telecom service by the service providers in the whole city/state/licensed service area.