



TELECOM REGULATORY AUTHORITY OF INDIA

Independent Drive Test Report

North East LSA

May 2026

Contents

1. Introduction	3
2. Executive Summary (LSA)	3
2.1 Drive test details	3
2.2 Drive test routes	4
2.3 Summary of areas covered	4
2.4 Telecom service providers detected frequency bands	5
2.5 Performance against key QoS parameters	5
3. QoS performance analysis-LSA level	6
3.1 Overview	7
3.2 Voice performance	7
3.3 Data performance	10
4. Detailed QoS performance analysis	12
4.1 Overview	12
4.2 City	12
4.2.1 Drive test route	12
4.2.2 Areas covered	12
4.2.3 Voice performance	13
4.2.4 Data performance	21
4.3 Hotspots	25
4.3.1 Locations	25
4.3.2 Hotspot covered	25
4.3.3 Voice performance	25
4.3.4 Data performance (Auto-selection mode 5G/4G/3G/2G)	27
4.3.5 Data performance (5G Only & 4G Only Download & Upload Speed)	30
4.4 Walk Test	33
4.4.1 Walk test locations	33
4.4.2 Walk Test Covered	33
4.4.3 Voice Performance	33
4.4.4 Data Performance	35
5. Voice & Data Key findings	37
5.1 Overall Voice	37
5.2 Overall Data	37
5.3 Operator wise Key Findings	38
6. Annexure	42

6.1 Route wise coverage map	42
6.1.1 City	42
7. Appendix	48
7.1 Appendix-I	48
7.1.1 Drive test setup	48
7.1.2 Drive test Methodology	50
7.2 Appendix-II	52
7.2.1 Network Performance Parameters for Voice calls	52
7.2.2 Network Performance Parameters Data tests	53

1. Introduction

TRAI Act, 1997 mandates the Authority to ensure the services delivered through various telecommunications networks meet the required quality standards prescribed, to protect the interest of the consumers of telecommunication services. TRAI is also responsible for conducting the periodical audit of such services provided by the service providers so as to protect the interests of the consumers of telecommunications services.

Accordingly, TRAI has engaged M/s RedMango Analytics Pvt. Ltd. to undertake assessment of Quality of Service of mobile service through Independent Drive Test (IDT).

In IDT, the performance of all service providers providing service in a Licensed Service Area (LSA) through various technologies (like 2G/ 3G/ 4G/ 5G) for voice and data are measured by conducting drive test. The drive test routes are finalised based on various objective criteria like reported network performance, consumer complaints etc. Methodology adopted for conducting IDT is elaborated in **APPENDIX-I**.

2. Executive Summary (LSA)

2.1 Drive test details

This report covers the findings of the IDT undertaken in North East License Service Area (LSA) during the month of May-2026 under the supervision of TRAI Regional Office (RO) Kolkata. Details of route/area covered during the IDT are as given below:

S. No	Drive test route	Type of route	Distance covered (KMs)	From date	To date
1	Cities and adjoining areas of South Tripura District	City	244.2	13-May-2026	15-May-2026
2	Belonia	Inter Operator Calling	1 Location	16-May-2026	16-May-2026
3	Cities and adjoining areas of South Tripura District	Hotspot	9 Locations	13-May-2026	15-May-2026
4	Belonia & Sabroom	Walk test	1.6	13-May-2026	15-May-2026

Table-1: Drive test summary.

2.2 Drive test routes

The map provides overview of drive test routes indicating city drive, inter-operator call test, hotspots and walk test as per the legends shown on the map.




Figure-1: Drive test routes.

2.3 Summary of areas covered

a) City- Rajnagar, Belonia, Paikhola, Rajapur, Santirbazar, Baikhora, Jolaibari, Gardhang, Bhuratali, Manu Bazar, Kalachara, Sabroom, Baishnabpur, Dakshin Manu Bankul and Matai etc.

b) Hotspot

1. Belonia Sub Post Office Bank Rd Opp. to Old Motor Stand Belonia
2. District Court Belonia
3. District Hospital Santirbazar
4. Iswar Chandra Vidyasagar College Belonia
5. Jolaibari BDO Office Muhuripur R.F.
6. Manu H.S. School Manu Bazar
7. Sabroom Sub-Divisional Hospital Sabroom
8. The Court of Additional District and Sessions Judge Sabroom
9. Trishna Wild Life Sanctuary Belonia Joychandrapur

c) Walk Test

1. Sabroom Railway Station Paschim Jalefa
2. Sub-Division Hospital Belonia

2.4 Telecom service providers detected frequency bands


Technologies covered during the IDT and frequency bands in use are summarised in table below:

S.no.	Name of TSP	Technology	Frequency Bands (In MHz)
1	Bharti Airtel Ltd.	2G	900
2	Bharti Airtel Ltd.	4G	900,1800,2100,2300
3	Bharti Airtel Ltd.	5G	3500
4	BSNL	2G	900
5	BSNL	3G	2100
6	BSNL	4G	700,2100,2500
7	Reliance JIO Infocomm Ltd.	4G	850,1800,2300
8	Reliance JIO Infocomm Ltd.	5G	700,3500
9	Vodafone Idea Ltd.	2G	1800
10	Vodafone Idea Ltd.	4G	1800

Table-2: Telecom service provider (TSP) covered in IDT.

2.5 Performance against key QoS parameters

CSSR: Call Setup Success Rate (in %), CST: Call Setup Time (in seconds), DCR: Drop Call Rate (in %) & MOS: Mean Opinion Score.



Summary-Voice services	Summary-Data services												
Call Setup Success Rate: Airtel, BSNL, RJIL and VIL have 82.15%, 56.93%, 100.00% and 46.46% call setup success rate respectively in Auto-selection mode (5G/4G/3G/2G). Call Setup Time: Airtel, BSNL, RJIL and VIL have call setup time of 2.56, 8.28, 0.71 and 2.54 seconds respectively in Auto-selection mode (5G/4G/3G/2G). Drop Call Rate: Airtel, BSNL, RJIL and VIL have drop call rate of 2.68%, 8.49%, 0.81% and 10.59% respectively in Auto-selection mode (5G/4G/3G/2G). Call Silence/Mute Rate: Airtel, BSNL, RJIL and VIL have silence call rate of 5.47%, 10.69%, 3.28% and 4.04% respectively in packet switched network (4G/5G). Mean Opinion Score (MOS): Airtel, BSNL, RJIL and VIL have average MOS of 3.95, 3.11, 4.31 and 4.56 respectively.	Summary-Data services Data Download performance (Overall): Average download speed of Airtel (5G/4G/2G) is 90.22 Mbps, BSNL (4G/3G/2G) is 11.28 Mbps, RJIL (5G/4G) is 55.89 Mbps and VIL (4G/2G) is 34.36 Mbps. Data Upload performance (Overall): Average upload speed of Airtel (5G/4G/2G) is 20.83 Mbps, BSNL (4G/3G/2G) is 3.60 Mbps, RJIL (5G/4G) is 4.13 Mbps and VIL (4G/2G) is 6.98 Mbps. Latency (Overall): Airtel, BSNL, RJIL and VIL 50th percentile latency is 60.42 ms, 60.75 ms, 61.29 ms and 53.61 ms respectively. Data performance - Hotspots (in Mbps): <table> <tr> <td>Airtel- 4G D/L: 57.13</td><td>4G U/L: 15.13</td></tr> <tr> <td>5G D/L: 109.13</td><td>5G U/L: 46.70</td></tr> <tr> <td>BSNL- 4G D/L: 18.48</td><td>4G U/L: 10.41</td></tr> <tr> <td>RJIL- 4G D/L: 25.09</td><td>4G U/L: 3.42</td></tr> <tr> <td>5G D/L: 94.49</td><td>5G U/L: 8.16</td></tr> <tr> <td>VIL- 4G D/L: 35.42</td><td>4G U/L: 8.71</td></tr> </table> Note- "D/L" Download speed, "U/L" Upload speed	Airtel- 4G D/L: 57.13	4G U/L: 15.13	5G D/L: 109.13	5G U/L: 46.70	BSNL- 4G D/L: 18.48	4G U/L: 10.41	RJIL- 4G D/L: 25.09	4G U/L: 3.42	5G D/L: 94.49	5G U/L: 8.16	VIL- 4G D/L: 35.42	4G U/L: 8.71
Airtel- 4G D/L: 57.13	4G U/L: 15.13												
5G D/L: 109.13	5G U/L: 46.70												
BSNL- 4G D/L: 18.48	4G U/L: 10.41												
RJIL- 4G D/L: 25.09	4G U/L: 3.42												
5G D/L: 94.49	5G U/L: 8.16												
VIL- 4G D/L: 35.42	4G U/L: 8.71												

- The Poor signal strength in auto-selection mode (5G/4G/3G/2G) during **voice** testing has been observed in 20.22%, 41.16%, 21.36% & 44.12% of the **City IDT route** (Cities and adjoining areas of South Tripura District) in case of Airtel, BSNL, RJIL and VIL respectively. {refer **figure- 39 to 42** as per the **Section 6.1** under Para-6 (Annexure)}
- The Poor signal strength in auto-selection mode (5G/4G/3G/2G) during **data** testing has been observed in 35.64%, 38.72%, 42.94% & 35.48% of the **City IDT route** (Cities and adjoining areas of South Tripura District) in case of Airtel, BSNL, RJIL and VIL respectively. {refer **figure- 43 to 46** as per the **Section 6.1** under Para-6 (Annexure)}

QoS Performance Analysis- North East LSA

3. QoS performance analysis-LSA level

3.1 Overview

This section provides summary of overall QoS performance of the telecom service provider's network in the LSA by aggregating the results of drive tests conducted in the North East LSA during the month of May-2026 covering city drive, hotspots and walk test. (Refer Table-1)

3.2 Voice performance

(a) Voice Call Performance in 3G/2G network mode only: 3G/2G network mode testing has been done to reflect experience for respective users as they have only 3G/2G compatible handsets.

Parameters	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
Call Attempts	289	410	367
Call Setup Success Rate %	69.90	25.37	48.77
Drop Call Rate %	0.99	18.27	11.17
Call Setup Time-Average (Second)	4.27	4.00	4.93
Handover Success Rate %	100.00	100.00	100.00

Table-3: Summary of voice call performance in 3G/2G network mode only.




Figure-2: Call setup success rate and drop call rate performance.

Number of unique cell Id's covered in Voice test- Technology wise			
Technology	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
3G	NA	21	NA
2G	183	108	93

Table-4: Technology wise number of network cell Id's latched during drive test.

Note-

- RJIL does not have 3G/2G network.
- NA- Service provider doesn't provide services in respective technology.

(b) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	409	476	369	508
Call Setup Success Rate %	82.15	56.93	100.00	46.46
Drop Call Rate %	2.68	8.49	0.81	10.59
Call Setup Time-Average (Second)	2.56	8.28	0.71	2.54
Handover Success Rate %	99.73	98.02	99.93	99.62

Table-5: Summary of voice call performance in network auto-selection mode.




Figure-3: Performance for call setup success rate and drop call rate.

Parameter	Service Provider			
	Mobile-to-Mobile (5G/4G - Open Mode)			
	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider Network)	201	131	244	99
Number of silences call for >4 Sec	11	14	8	4
Silence Call Rate %	5.47	10.69	3.28	4.04
Number of silence instances for >4 Sec	16	15	14	6
Number of silence instances for >3 Sec	17	24	20	6
Number of silence instances for >2 sec	24	33	29	8
RTP Jitter (4G & 5G) in ms	5.56	6.73	13.27	7.98
Packet loss Rate Downlink %	1.80	7.41	3.38	1.71
Packet loss Rate Uplink %	1.33	3.45	2.28	1.11

Table-6: Summary of silence instances & packet loss rate for mobile to mobile calls.

Number of unique cell Id's covered in Voice test- Technology wise				
Technology	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
5G	0	NA	48	NA
4G	543	161	506	123
3G	NA	11	NA	NA
2G	12	28	NA	75

Table-7: Technology wise number of network cell Id's latched during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.
- 0- No cell Id's were found in respective technology.

(c) Mean Opinion Score (MOS) performance for speech quality:

Mean opinion score indicates quality of speech observed during the drive test across different technologies. This parameter has been calculated for mobile-to-mobile calls made within same operator network in auto mode (5G/4G/3G/2G). As per ITU-T Recommendation P.863.1, MOS values means: 5-Excellent, 4-Good, 3-Fair, 2-Poor, 1-Bad.

Speech Quality (MOS) distribution	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
Total Number of MOS Samples for calls table-6	1739	946	2093	825
Speech Quality (Average MOS)	3.95	3.11	4.31	4.56
Number of samples with MOS ≥ 4 to <5 (Excellent)	1427	366	1728	759
Number of samples with MOS ≥ 3 to <4 (Good)	246	169	166	36
Number of samples with MOS ≥ 2 to <3 (Fair)	13	213	69	9
Number of samples with MOS ≥ 1 to <2 (Poor)	53	198	130	21
%age of samples with MOS ≥ 4 to <5 (Excellent)	82.06%	38.69%	82.56%	92.00%
%age of samples with MOS ≥ 3 to <4 (Good)	14.15%	17.86%	7.93%	4.36%
%age of samples with MOS ≥ 2 to <3 (Fair)	0.75%	22.52%	3.30%	1.09%
%age of samples with MOS ≥ 1 to <2 (Poor)	3.05%	20.93%	6.21%	2.55%

Table-8: Summary of speech quality (MOS) samples.




Figure- 4: Distribution of samples in MOS range.

(d) Inter-service provider voice call performance: To check the performance of inter-service providers call setup success rate, total 15 inter operator calls were attempted at one location which is V-Mart, Belonia market. The call setup success rate and call setup time observation is as below.

Call Setup Success Rate %				
From Service Provider	To Service Provider			
	AIRTEL	BSNL	RJIL	VIL
AIRTEL	NA	100.00	100.00	100.00
BSNL	100.00	NA	100.00	100.00
RJIL	100.00	100.00	NA	100.00
VIL	100.00	100.00	100.00	NA

Table-9: Call setup success rate across service providers.

Note-

- NA- Only inter-operator calls were measured during test.

Call setup time average (seconds)				
From Service Provider	To Service Provider			
	AIRTEL	BSNL	RJIL	VIL
AIRTEL	NA	3.12	1.53	3.29
BSNL	8.29	NA	7.85	6.22
RJIL	1.94	2.72	NA	1.88
VIL	1.64	5.51	1.94	NA

Table-10: Call setup time across service providers.

Note-

- NA- Only inter-operator calls were measured during test.

3.3 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbits/s)	Average	90.22	11.28	55.89	34.36
	80th Percentile	170.67	19.52	52.30	46.75
	20th Percentile	13.17	3.43	3.64	17.10
Upload Throughput (Mbits/s)	Average	20.83	3.60	4.13	6.98
	80th Percentile	41.58	5.62	4.67	9.75
	20th Percentile	1.61	1.22	1.21	2.02
Latency (ms)	50th Percentile	60.42	60.75	61.29	53.61

Table-11: Summary of data performance in network auto-selection mode.




Figure- 5: Download and Upload throughput

Number of unique cell Id's covered in Data test- Technology wise				
Technology	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
5G	0	NA	68	NA
4G	535	181	408	161
3G	NA	12	NA	NA
2G	5	46	NA	85

Table-12: Technology wise number of network cell Id's latched during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.
- 0- No cell Id's were found in respective technology.

Detailed QoS Performance Analysis

4. Detailed QoS performance analysis

4.1 Overview

This section covers analysis on performance of various categories of drives like city, hotspots and walk test for all telecom service providers, the results of drive tests conducted are shown individually for respective areas/locations.

4.2 City

Drive test has been conducted from 13th May 2026 to 15th May 2026 in cities and adjoining areas of South Tripura District. (Refer Table-1)

4.2.1 Drive test route




Figure- 6: Drive test routes.

4.2.2 Areas covered

Rajnagar, Belonia, Paikhola, Rajapur, Santirbazar, Baikhora, Jolaibari, Gardhang, Bhuratali, Manu Bazar, Kalachara, Sabroom, Baishnabpur, Dakshin Manu Bankul and Matai etc.

4.2.3 Voice performance

(a) Voice Call Performance in 3G/2G network mode only: 3G/2G network mode testing has been done to reflect experience for respective users as they have only 3G/2G compatible handsets.

Parameters	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
Call Attempts	289	410	367
Call Setup Success Rate %	69.90	25.37	48.77
Drop Call Rate %	0.99	18.27	11.17
Call Setup Time-Average (Second)	4.27	4.00	4.93
Handover Success Rate %	100.00	100.00	100.00

Table-13: Summary of voice call performance in 3G/2G network mode only.




Figure-7: Performance for call setup success rate.




Figure-8: Performance for drop call rate.

(b) Network Technology: This section represent time spent on various network technologies.

Technology	Service Provider		
	AIRTEL	BSNL	VIL
3G	NA	19.05%	NA
2G	91.96%	58.75%	81.87%
Limited Service	8.04%	22.20%	18.13%

Table-14: Time spent on technology during drive test 3G/2G network mode.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-9: Serving technology plots 3G/2G network mode - AIRTEL.




Figure-10: Serving technology plots 3G/2G network mode - BSNL.

(d) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	294	360	254	393
Call Setup Success Rate %	75.17	48.89	100.00	37.66
Drop Call Rate %	4.07	12.50	0.79	16.22
Call Setup Time Average (Second)	2.68	8.48	0.78	3.09
Handover Success Rate %	99.68	97.35	99.96	99.60

Table-15: Summary of voice call performance in network auto-selection mode.




Figure-13: Performance for call setup success rate.




Figure-14: Performance for drop call rate.

Parameter	Service Provider			
	Mobile-to-Mobile (5G/4G - Open Mode)			
	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider Network)	201	131	244	99
Number of silences call for >4 Sec	11	14	8	4
Silence Call Rate %	5.47	10.69	3.28	4.04
Number of silence instances for >4 Sec	16	15	14	6
Number of silence instances for >3 Sec	17	24	20	6
Number of silence instances for >2 sec	24	33	29	8
RTP Jitter (4G & 5G) in ms	5.56	6.73	13.27	7.98
Packet loss Rate Downlink %	1.80	7.41	3.38	1.71
Packet loss Rate Uplink %	1.33	3.45	2.28	1.11

Table-16: Summary of silence instances & packet loss rate for mobile to mobile call.

(e) Mean Opinion Score (MOS) performance for speech quality:

Mean opinion score indicates quality of speech observed during the drive test across different technologies. This parameter has been calculated for mobile to mobile calls made within same operator network in auto mode (5G/4G/3G/2G). As per ITU-T Recommendation P.863.1, MOS value means: 5-Excellent, 4-Good, 3-Fair, 2-Poor, 1-Bad.

Speech Quality (MOS) distribution	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
Total Number of MOS Samples for calls in table-16	1739	946	2093	825
Speech Quality (Average MOS)	3.95	3.11	4.31	4.56
Number of samples with MOS >=4 to <5 (Excellent)	1427	366	1728	759
Number of samples with MOS >=3 to <4 (Good)	246	169	166	36
Number of samples with MOS >=2 to <3 (Fair)	13	213	69	9
Number of samples with MOS >=1 to <2 (Poor)	53	198	130	21
%age of samples with MOS >=4 to <5 (Excellent)	82.06%	38.69%	82.56%	92.00%
%age of samples with MOS >=3 to <4 (Good)	14.15%	17.86%	7.93%	4.36%
%age of samples with MOS >=2 to <3 (Fair)	0.75%	22.52%	3.30%	1.09%
%age of samples with MOS >=1 to <2 (Poor)	3.05%	20.93%	6.21%	2.55%

Table-17: Summary of speech quality (MOS) samples.




Figure-15: Distribution of samples in MOS range.

(f) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	0.93%	NA	16.13%	NA
4G	87.59%	74.78%	83.87%	42.15%
3G	NA	5.53%	NA	NA
2G	1.39%	10.23%	NA	24.73%
Limited Service	10.09%	9.46%	0.00%	33.12%

Table-18: Time spent on technology during drive test in auto-selection mode (5G/4G/3G/2G) voice.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-16: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - AIRTEL.




Figure-17: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - BSNL.




Figure-18: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - RJIL.




Figure-19: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - VIL.

(g) Network Signal Strength Distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G) voice. (Refer figure-39, 40, 41 & 42 for map view)




Figure-20: Signal strength distribution auto-selection mode (5G/4G/3G/2G) voice.

Observations:

- Airtel has 14% of samples falling in the excellent signal strength category.
- BSNL has 6% of samples falling in the excellent signal strength category.
- RJIL has 16% of samples falling in the excellent signal strength category.
- VIL has 6% of samples falling in the excellent signal strength category.

4.2.4 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbits/s)	Average	88.67	10.64	46.11	35.19
	80th Percentile	167.31	18.80	43.45	46.71
	20th Percentile	12.77	2.73	3.85	18.88
Upload Throughput (Mbits/s)	Average	17.32	3.25	3.83	6.84
	80th Percentile	23.38	3.99	4.57	9.71
	20th Percentile	1.59	1.21	1.21	2.20
Latency (ms)	50th Percentile	59.58	59.85	67.09	52.00

Table-19: Summary of Data performance in network auto-selection mode.




Figure- 21: Download throughput.




Figure- 22: Upload throughput.

(b) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	33.17%	NA	19.28%	NA
4G	50.41%	59.50%	79.74%	31.90%
3G	NA	12.81%	NA	NA
2G	0.17%	1.87%	NA	11.56%
Limited Service	16.25%	25.82%	0.98%	56.54%

Table-20: Time spent on technology during drive test in auto-selection mode (5G/4G/3G/2G) data.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-23: Serving technology plots in auto-selection mode (5G/4G/3G/2G) data - AIRTEL.




Figure-24: Serving technology plots in auto-selection mode (5G/4G/3G/2G) data - BSNL.




Figure-25: Serving technology plots in auto-selection mode (5G/4G/3G/2G) data - RJIL.




Figure-26: Serving technology plots in auto-selection mode (5G/4G/3G/2G) data - VIL.

(c) Network Signal Strength Distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G) data. (Refer figure-43, 44, 45 & 46 for map view)




Figure-27: Signal strength distribution auto-selection mode (5G/4G/3G/2G) data.

Observations:

- Airtel has 6% of samples falling in the excellent signal strength category.
- BSNL has 4% of samples falling in the excellent signal strength category.
- RJIL has 5% of samples falling in the excellent signal strength category.
- VIL has 1% of samples falling in the excellent signal strength category.

4.3 Hotspots

Hotspot testing has been conducted from 13th May 2026 to 15th May 2026. Nine locations have been tested in cities and adjoining areas of South Tripura District. (Refer Table-1)

4.3.1 Locations




Figure- 28: Hotspot locations.

4.3.2 Hotspot covered

1. Belonia Sub Post Office Bank Rd Opp. to Old Motor Stand Belonia
2. District Court Belonia
3. District Hospital Santirbazar
4. Iswar Chandra Vidyasagar College Belonia
5. Jolaibari BDO Office Muhuripur R.F.
6. Manu H.S. School Manu Bazar
7. Sabroom Sub-Divisional Hospital Sabroom
8. The Court of Additional District and Sessions Judge Sabroom
9. Trishna Wild Life Sanctuary Belonia Joychandrapur

4.3.3 Voice performance

Overall Voice Performance				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	90	90	90	90
Call Setup Success Rate %	100.00	81.11	100.00	78.89
Drop Call Rate %	0.00	1.37	1.11	1.41
Call Setup Time-Average (Second)	2.34	8.06	0.54	1.67

Table-21: Overall summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Belonia Sub Post Office Bank Rd Opp. to Old Motor Stand Belonia				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	90.00	100.00	70.00
Drop Call Rate %	0.00	0.00	10.00	0.00
Call Setup Time-Average (Second)	2.37	5.54	0.61	1.38

Table-22: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G).

District Court Belonia				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	80.00	100.00	80.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	2.37	6.57	0.49	1.24

Table-23: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G).

District Hospital Santirbazar				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	70.00	100.00	80.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	2.25	8.12	0.54	1.23

Table-24: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G).

Iswar Chandra Vidyasagar College Belonia				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	90.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	2.42	8.40	0.55	1.11

Table-25: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G).

Jolaibari BDO Office Muhuripur R.F.				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	80.00	100.00	80.00
Drop Call Rate %	0.00	0.00	0.00	12.50
Call Setup Time-Average (Second)	2.26	8.25	0.51	1.39

Table-26: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G).

Manu H.S. School Manu Bazar				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	2.23	8.39	0.53	1.30

Table-27: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G).

Sabroom Sub-Divisional Hospital Sabroom				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	70.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	2.37	8.63	0.56	1.41

Table-28: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G).

The Court of Additional District and Sessions Judge Sabroom				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	90.00	100.00	70.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	2.32	8.58	0.51	1.46

Table-29: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G).

Trishna Wild Life Sanctuary Belonia Joychandrapur				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	30.00	100.00	60.00
Drop Call Rate %	0.00	33.33	0.00	0.00
Call Setup Time-Average (Second)	2.45	13.26	0.61	5.61

Table-30: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G).

4.3.4 Data performance (Auto-selection mode 5G/4G/3G/2G)

Overall Data Performance				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	122.38	15.27	83.79	37.62
Download Throughput 80th Percentile (Mbit/s)	178.11	21.14	86.23	46.74
Download Throughput 20th Percentile (Mbit/s)	41.57	8.51	3.61	30.27
Download Session Setup Success Rate %	100.00	97.78	95.56	82.22
Upload Throughput Average (Mbits/s)	35.78	4.61	6.29	8.21
Upload Throughput 80th Percentile (Mbit/s)	70.49	6.46	11.82	9.76
Upload Throughput 20th Percentile (Mbit/s)	4.91	2.50	1.63	9.28
Upload Session Setup Success Rate %	100.00	100.00	100.00	82.22
Web Browsing Delay (Second)	4.45	4.44	3.62	2.97
Youtube Initial Buffer Delay (Second)	0.88	1.18	2.98	1.32
Latency (ms) - 50th Percentile	61.37	60.64	57.12	53.95
Jitter (ms)	8.80	13.18	40.90	6.35
Packet Loss Rate%	6.56	12.14	18.63	22.46
Packet Loss Rate- 90th percentile	14.48	42.46	56.74	100.00

Table-31: Overall Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Belonia Sub Post Office Bank Rd Opp. to Old Motor Stand Belonia				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	180.82	1.97	36.79	44.66
Download Session Setup Success Rate %	100.00	80.00	100.00	100.00
Upload Throughput Average (Mbits/s)	87.16	2.34	2.55	9.63
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	4.59	4.29	3.86	3.95
Youtube Initial Buffer Delay (Second)	0.72	2.91	2.24	0.75
Latency (ms) - 50th Percentile	63.18	68.11	54.40	50.95
Jitter (ms)	5.96	19.93	99.90	6.44
Packet Loss Rate%	16.20	45.20	12.10	0.20

Table-32: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

District Court Belonia				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	68.40	5.41	7.08	30.21
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	12.10	1.55	4.09	2.30
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	4.21	3.68	3.21	1.95
Youtube Initial Buffer Delay (Second)	0.87	-	2.48	4.62
Latency (ms) - 50th Percentile	65.62	72.46	58.77	59.56
Jitter (ms)	18.07	59.92	31.05	13.35
Packet Loss Rate%	5.60	37.00	15.00	1.40

Table-33: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note--"Youtube tests were failed.

District Hospital Santirbazar				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	121.01	15.31	111.91	46.32
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	72.64	5.63	6.53	9.69
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	3.20	6.40	4.58	4.16
Youtube Initial Buffer Delay (Second)	0.73	0.88	5.26	0.72
Latency (ms) – 50 th Percentile	63.67	58.37	51.65	54.54
Jitter (ms)	7.69	11.78	24.19	5.85
Packet Loss Rate%	0.50	0.10	5.30	0.10

Table-34: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Iswar Chandra Vidyasagar College Belonia				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	121.59	19.41	18.44	41.12
Download Session Setup Success Rate %	100.00	100.00	60.00	100.00
Upload Throughput Average (Mbits/s)	6.78	5.04	1.65	9.74
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	3.30	1.74	-	1.81
Youtube Initial Buffer Delay (Second)	1.36	0.88	-	0.79
Latency (ms) - 50th Percentile	56.14	65.35	95.18	53.20
Jitter (ms)	7.37	6.62	114.09	4.82
Packet Loss Rate%	0.50	0.40	50.30	0.00

Table-35: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note--"Web Browsing & Youtube all tests were failed.

Jolaibari BDO Office Muhuripur R.F.				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	69.13	12.21	532.31	29.32
Download Session Setup Success Rate%	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	16.96	2.88	20.25	9.68
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	6.31	4.36	3.98	1.90
Youtube Initial Buffer Delay (Second)	1.18	2.30	1.01	0.74
Latency (ms)- 50th Percentile	50.59	56.88	50.94	50.68
Jitter (ms)	11.66	2.84	2.51	4.03
Packet Loss Rate%	5.40	0.10	0.60	0.10

Table-36: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Manu H.S. School Manu Bazar				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	154.47	18.81	2.99	41.82
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	30.98	4.48	3.70	9.62
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	3.65	4.58	1.91	1.42
Youtube Initial Buffer Delay (Second)	0.80	0.84	2.28	0.72
Latency (ms) - 50th Percentile	69.15	55.98	61.79	51.33
Jitter (ms)	4.77	1.94	30.84	4.35
Packet Loss Rate%	0.30	0.70	2.30	0.30

Table-37: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Sabroom Sub-Divisional Hospital Sabroom				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	211.54	20.14	3.70	43.94
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	72.98	5.10	14.20	9.64
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	3.16	4.92	1.79	4.91
Youtube Initial Buffer Delay (Second)	0.74	0.90	0.91	0.87
Latency (ms) – 50 th Percentile	58.55	67.80	50.22	56.93
Jitter (ms)	4.85	8.58	2.70	5.61
Packet Loss Rate%	0.10	0.80	1.70	0.00

Table-38: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

The Court of Additional District and Sessions Judge Sabroom				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	149.69	20.51	8.04	2.53
Download Session Setup Success Rate %	100.00	100.00	100.00	40.00
Upload Throughput Average (Mbits/s)	21.40	7.56	2.62	1.14
Upload Session Setup Success Rate %	100.00	100.00	100.00	20.00
Web Browsing Delay (Second)	3.45	3.21	1.74	1.51
Youtube Initial Buffer Delay (Second)	0.61	0.93	6.04	-
Latency (ms) - 50th Percentile	53.19	62.53	59.73	-
Jitter (ms)	4.91	5.03	12.77	-
Packet Loss Rate%	0.10	0.10	1.60	100.00

Table-39: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "Web Browsing, Youtube & ping all tests were failed.

Trishna Wild Life Sanctuary Belonia Joychandrapur				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	24.73	20.98	6.70	-
Download Session Setup Success Rate%	100.00	100.00	100.00	0.00
Upload Throughput Average (Mbits/s)	1.03	6.91	1.04	1.17
Upload Session Setup Success Rate %	100.00	100.00	100.00	20.00
Web Browsing Delay (Second)	9.99	5.39	15.73	-
Youtube Initial Buffer Delay (Second)	-	0.86	-	-
Latency (ms)- 50th Percentile	72.32	58.58	105.22	-
Jitter (ms)	13.88	2.31	49.47	-
Packet Loss Rate%	30.30	24.90	78.80	100.00

Table-40: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note- "Respective tests were failed.

4.3.5 Data performance (5G Only & 4G Only Download & Upload Speed)

Overall Data Performance					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	109.13	-	94.49	-
	Upload Throughput Average (Mbits/s)	46.70	-	8.16	-
4G	Download Throughput Average (Mbits/s)	57.13	18.48	25.09	35.42
	Upload Throughput Average (Mbits/s)	15.13	10.41	3.42	8.71

Table-41: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "Respective technology was not observed during the test.

Belonia Sub Post Office Bank Rd Opp. to Old Motor Stand Belonia					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	137.84	-	87.08	-
	Upload Throughput Average (Mbits/s)	94.53	-	6.76	-
4G	Download Throughput Average (Mbits/s)	77.17	10.73	5.84	42.34
	Upload Throughput Average (Mbits/s)	6.25	4.50	1.72	9.63

Table-42: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

District Court Belonia					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	51.85	-	4.52	-
	Upload Throughput Average (Mbits/s)	13.62	-	3.27	-
4G	Download Throughput Average (Mbits/s)	20.57	18.66	8.44	27.69
	Upload Throughput Average (Mbits/s)	6.65	4.49	3.34	7.51

Table-43: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

District Hospital Santirbazar					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	93.25	-	99.10	-
	Upload Throughput Average (Mbits/s)	69.69	-	4.44	-
4G	Download Throughput Average (Mbits/s)	28.73	27.00	31.22	46.99
	Upload Throughput Average (Mbits/s)	15.53	22.27	2.83	9.63

Table-44: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Iswar Chandra Vidyasagar College Belonia					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	107.45	-	78.19	-
	Upload Throughput Average (Mbits/s)	7.26	-	2.05	-
4G	Download Throughput Average (Mbits/s)	24.74	22.25	9.31	41.79
	Upload Throughput Average (Mbits/s)	2.99	6.78	1.41	9.63

Table-45: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Jolaibari BDO Office Muhuripur R.F.					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	43.15	-	530.57	-
	Upload Throughput Average (Mbits/s)	23.72	-	24.71	-
4G	Download Throughput Average (Mbits/s)	35.95	11.15	90.29	26.97
	Upload Throughput Average (Mbits/s)	16.91	6.02	3.44	9.62

Table-46: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Manu H.S. School Manu Bazar					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	119.66	-	3.49	-
	Upload Throughput Average (Mbits/s)	39.47	-	2.16	-
4G	Download Throughput Average (Mbits/s)	57.92	18.73	58.53	37.07
	Upload Throughput Average (Mbits/s)	12.18	12.58	7.64	9.59

Table-47: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Sabroom Sub-Divisional Hospital Sabroom					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	202.12	-	4.11	-
	Upload Throughput Average (Mbits/s)	83.91	-	19.50	-
4G	Download Throughput Average (Mbits/s)	114.97	21.17	2.86	42.54
	Upload Throughput Average (Mbits/s)	49.93	7.75	5.34	9.60

Table-48: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

The Court of Additional District and Sessions Judge Sabroom					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	95.85	-	3.37	-
	Upload Throughput Average (Mbits/s)	29.66	-	7.62	-
4G	Download Throughput Average (Mbits/s)	123.16	15.77	3.32	6.28
	Upload Throughput Average (Mbits/s)	23.22	7.91	4.07	1.59

Table-49: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Trishna Wild Life Sanctuary Belonia Joychandrapur					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	-	-	3.58	-
	Upload Throughput Average (Mbits/s)	-	-	1.56	-
4G	Download Throughput Average (Mbits/s)	30.97	20.91	16.02	-
	Upload Throughput Average (Mbits/s)	2.55	21.44	0.98	-

Table-50: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

4.4 Walk Test

Walk test has been conducted on 13th May 2026 & 15th May 2026. Two locations have been tested in Belonia & Sabroom cities. (Refer Table-1)

4.4.1 Walk test locations



Figure-29: Walk Test locations.

4.4.2 Walk Test Covered

1. Sabroom Railway Station Paschim Jalefa
2. Sub-Division Hospital Belonia

4.4.3 Voice Performance

i) Sabroom Railway Station Paschim Jalefa

(a) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Sabroom Railway Station Paschim Jalefa				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	12	13	12	12
Call Setup Success Rate %	100.00	92.31	100.00	58.33
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	2.46	5.98	0.81	1.60
Handover Success Rate %	100.00	100.00	100.00	100.00

Table-51: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).




Figure- 30: Performance for call setup success rate and drop call rate.

(b) Network Technology: This section represents time spent on various network technologies.

Sabroom Railway Station Paschim Jalefa				
Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	0.86%	NA	4.24%	NA
4G	99.14%	45.73%	95.76%	92.95%
3G	NA	31.34%	NA	NA
2G	0.00%	22.93%	NA	0.00%
Limited service	0.00%	0.00%	0.00%	7.05%

Table-52: Time spent on technology during walk test.

(c) Network Signal Strength distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G).




Figure-31: Signal strength distribution auto-selection mode (5G/4G/3G/2G).

ii) Sub-Division Hospital Belonia

(a) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Sub-Division Hospital Belonia				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	13	13	13	13
Call Setup Success Rate %	100.00	76.92	100.00	76.92
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	2.31	9.07	0.54	1.26
Handover Success Rate %	100.00	100.00	100.00	-

Table-53: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Note- "-"Handover did not attempt.




Figure- 32: Performance for call setup success rate and drop call rate.

(b) Network Technology: This section represents time spent on various network technologies.

Sub-Division Hospital Belonia				
Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	5.62%	NA	93.56%	NA
4G	94.38%	100.00%	6.44%	100.00%
3G	NA	0.00%	NA	NA
2G	0.00%	0.00%	NA	0.00%
Limited service	0.00%	0.00%	0.00%	0.00%

Table-54: Time spent on technology during walk test.

(c) Network Signal Strength distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G).




Figure-33: Signal strength distribution auto-selection mode (5G/4G/3G/2G).

4.4.4 Data Performance

i) Sabroom Railway Station Paschim Jalefa

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Sabroom Railway Station Paschim Jalefa				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbps/s)	13.66	6.25	4.01	2.13
Download Throughput 80th Percentile	12.38	9.85	8.39	3.27
Download Throughput 20th Percentile	5.77	2.36	0.93	1.37
Download Session Setup Success Rate %	100.00	71.43	91.67	64.71
Upload Throughput Average (Mbps/s)	4.75	1.71	1.21	0.72
Upload Throughput 80th Percentile	9.61	1.92	1.40	1.45
Upload Throughput 20th Percentile	1.86	1.11	0.85	0.08
Upload Session Setup Success Rate %	100.00	100.00	91.67	64.71
Latency (ms)-50th Percentile	68.58	70.42	252.07	63.86

Table-55: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).




Figure- 34: Download and Upload throughput.

ii) Sub-Division Hospital Belonia

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Sub-Division Hospital Belonia				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	80.04	7.81	172.26	46.17
Download Throughput 80th Percentile	178.80	10.90	191.91	46.99
Download Throughput 20th Percentile	21.63	3.68	159.58	45.33
Download Session Setup Success Rate %	100.00	92.86	100.00	100.00
Upload Throughput Average (Mbits/s)	41.51	6.60	4.23	9.72
Upload Throughput 80th Percentile	52.46	7.87	3.94	9.78
Upload Throughput 20th Percentile	25.81	5.94	2.75	9.66
Upload Session Setup Success Rate %	100.00	92.31	100.00	100.00
Latency (ms)-50th Percentile	53.80	61.70	49.95	54.27

Table-56: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).




Figure- 35: Download and Upload throughput.

5. Voice & Data Key findings

5.1 Overall Voice

1. Call Setup Success Rate:

- a) Airtel, BSNL and VIL have 69.90%, 25.37% and 48.77% call setup success rate respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL and VIL have 82.15%, 56.93%, 100.00% and 46.46% call setup success rate respectively in auto-selection mode (5G/4G/3G/2G). (refer table-5)
- c) All operators have 100.00% call setup success rate while calling on peer service provider's network for inter-operator calls. (refer table-9)

2. Call Setup Time:

- a) Airtel, BSNL and VIL call setup time is 4.27, 4.00 and 4.93 seconds respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL & VIL call setup time is 2.56, 8.28, 0.71 & 2.54 seconds respectively in auto-selection mode (5G/4G/3G/2G). (refer table-5)

3. Call Silence/Mute Rate:

In packet switched network (4G/5G) Airtel, BSNL, RJIL and VIL have 5.47%, 10.69%, 3.28% and 4.04% silence call rate respectively. Further Airtel, BSNL, RJIL & VIL downlink RTP packet loss is 1.80%, 7.41%, 3.38% and 1.71% respectively. In uplink Airtel, BSNL, RJIL & VIL RTP packet loss is 1.33%, 3.45%, 2.28% & 1.11% respectively. (refer table-6)

4. Drop Call Rate:

- a) Airtel, BSNL and VIL drop call rate is 0.99%, 18.27% and 11.17% respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL and VIL drop call rate is 2.68%, 8.49%, 0.81% and 10.59% respectively in auto-selection mode (5G/4G/3G/2G). (refer table-5)

5.2 Overall Data

1. Data download and upload performance (Overall i.e. LSA):

- a) Airtel, BSNL, RJIL and VIL average download speeds are 90.22 Mbps, 11.28 Mbps, 55.89 Mbps and 34.36 Mbps respectively. (refer table-11)
- b) Airtel, BSNL, RJIL and VIL average upload speeds are 20.83 Mbps, 3.60 Mbps, 4.13 Mbps and 6.98 Mbps respectively. (refer table-11)

2. Data download and upload performance (static i.e. while stationary):

- a) Airtel, BSNL, RJIL and VIL average download speeds are 122.38 Mbps, 15.27 Mbps, 83.79 Mbps and 37.62 Mbps respectively. (refer table-31)
- b) Airtel, BSNL, RJIL and VIL average upload speeds are 35.78 Mbps, 4.61 Mbps, 6.29 Mbps and 8.21 Mbps respectively. (refer table-31)

3. Data session setup success rate (static i.e. while stationary):

- a) Airtel, BSNL, RJIL and VIL have 100.00%, 97.78%, 95.56% & 82.22% download session setup success rate respectively. (refer table-31)
- b) Airtel, BSNL, RJIL and VIL have 100.00%, 100.00%, 100.00% & 82.22% upload session setup success rate respectively. (refer table-31)

5.3 Operator wise Key Findings

1. Airtel:

Voice

- 69.90% call setup success rate and 0.99% drop call rate have been observed in 3G/2G network mode for LSA/city drive. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-3 & 13)
- 82.15% call setup success rate and 2.68% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-5)
- 75.17% call setup success rate and 4.07% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-15)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-21)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at both walk test locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-51 & 53)

Data

- Airtel has 90.22 Mbps average download speed & 20.83 Mbps average upload speed for LSA. (refer table-11)
- Airtel has 88.67 Mbps average download speed & 17.32 Mbps average upload speed across measured routes for city drive. (refer table-19)
- District Court Belonia, Jolaibari BDO Office Muhuripur R.F. and Trishna Wild Life Sanctuary Belonia Joychandrapur have less download speed (less than 100 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-33, 36 & 40)
- District Court Belonia, Iswar Chandra Vidyasagar College Belonia, Jolaibari BDO Office Muhuripur R.F. and Trishna Wild Life Sanctuary Belonia Joychandrapur have less upload speed (less than 20 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-33, 35, 36 & 40)
- Both walk test locations have less download speed (less than 100 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-55 & 56)
- Sabroom Railway Station Paschim Jalefa has less upload speed (less than 20 Mbps) out of total 2 walk test locations for auto-selection mode (5G/4G/3G/2G). (refer table-55)

2. BSNL:

Voice

- 25.37% call setup success rate and 18.27% drop call rate have been observed in 3G/2G network mode for LSA/city drive. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-3 & 13)
- 56.93% call setup success rate and 8.49% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-5)

- 48.89% call setup success rate and 12.50% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-15)
- 81.11% call setup success rate and 1.37% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-21)
- 92.31% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at Sabroom Railway Station Paschim Jalefa walk test location. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-51)
- 76.92% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at Sub-Division Hospital Belonia walk test location. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-53)

Data

- BSNL has 11.28 Mbps average download speed & 3.60 Mbps average upload speed for LSA. (refer table-11)
- BSNL has 10.64 Mbps average download speed & 3.25 Mbps average upload speed across measured routes for city drive. (refer table-19)
- Belonia Sub Post Office Bank Rd Opp. to Old Motor Stand Belonia and District Court Belonia have less download speed (less than 10 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-32 & 33)
- District Court Belonia has less upload speed (less than 2 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-33)
- Both walk test locations have less download speed (less than 10 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-55 & 56)
- Sabroom Railway Station Paschim Jalefa has less upload speed (less than 2 Mbps) out of total 2 walk test locations for auto-selection mode (5G/4G/3G/2G). (refer table-55)

3. RJIL: Voice

- 100.00% call setup success rate and 0.81% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-5)
- 100.00% call setup success rate and 0.79% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-15)
- 100.00% call setup success rate and 1.11% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-21)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at both walk test locations. Performance is well within the benchmark of 98.00% & 2.00% respectively. (refer table-51 & 53)

Data

- RJIL has 55.89 Mbps average download speed & 4.13 Mbps average upload speed for LSA. (refer table-11)
- RJIL has 46.11 Mbps average download speed & 3.83 Mbps average upload speed across measured routes for city drive. (refer table-19)
- All hotspot locations have less download speed (less than 100 Mbps) except District Hospital Santirbazar and Jolaibari BDO Office Muhuripur R.F. for auto-selection mode (5G/4G/3G/2G). (refer table-32, 33, 35, 37, 38, 39 & 40)
- All hotspot locations have less upload speed (less than 20 Mbps) except Jolaibari BDO Office Muhuripur R.F. for auto-selection mode (5G/4G/3G/2G). (refer table-32, 33, 34, 35, 37, 38, 39 & 40)
- Sabroom Railway Station Paschim Jalefa has less download speed (less than 100 Mbps) out of total 2 walk test locations for auto-selection mode (5G/4G/3G/2G). (refer table-55)
- Both walk test locations have less upload speed (less than 20 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-55 & 56)

4. VIL: Voice

- 48.77% call setup success rate and 11.17% drop call rate have been observed in 3G/2G network mode for LSA/city drive. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-3 & 13)
- 46.46% call setup success rate and 10.59% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-5)
- 37.66% call setup success rate and 16.22% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is not meeting the benchmark of 98.00% & 2.00% respectively. (refer table-15)
- 78.89% call setup success rate and 1.41% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-21)
- 58.33% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at Sabroom Railway Station Paschim Jalefa walk test location. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-51)
- 76.92% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) at Sub-Division Hospital Belonia walk test location. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-53)



Data

- VIL has 34.36 Mbps average download speed & 6.98 Mbps average upload speed for LSA. (refer table-11)
- VIL has 35.19 Mbps average download speed & 6.84 Mbps average upload speed across measured routes for city drive. (refer table-19)
- The Court of Additional District and Sessions Judge Sabroom and Trishna Wild Life Sanctuary Belonia Joychandrapur have less download speed (less than 10

Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-39 & 40)

- The Court of Additional District and Sessions Judge Sabroom and Trishna Wild Life Sanctuary Belonia Joychandrapur have less upload speed (less than 2 Mbps) out of total 13 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-39 & 40)
- Sabroom Railway Station Paschim Jalefa has less download speed (less than 10 Mbps) out of total 2 walk test locations for auto-selection mode (5G/4G/3G/2G). (refer table-55)
- Sabroom Railway Station Paschim Jalefa has less upload speed (less than 2 Mbps) out of total 2 walk test locations for auto-selection mode (5G/4G/3G/2G). (refer table-55)

6.1.1 City






Figure-38: Signal strength 3G/2G network mode voice - VIL.




Figure-39: Signal strength auto-selection mode (5G/4G/3G/2G) voice - AIRTEL.




Figure-40: Signal strength auto-selection mode (5G/4G/3G/2G) voice - BSNL.




Figure-41: Signal strength auto-selection mode (5G/4G/3G/2G) voice - RJIL.




Figure-42: Signal strength auto-selection mode (5G/4G/3G/2G) voice - VIL.




Figure-43: Signal strength auto-selection mode (5G/4G/3G/2G) data - AIRTEL.




Figure-44: Signal strength auto-selection mode (5G/4G/3G/2G) data - BSNL.




Figure-45: Signal strength auto-selection mode (5G/4G/3G/2G) data - RJIL.




Figure-46: Signal strength auto-selection mode (5G/4G/3G/2G) data - VIL.

7. Appendix

The details of the setup used for conducting the drive test and the network or performance parameters captured under different conditions may be seen at Appendix-I. The calculation method of each QoS parameter is given in Appendix-II of the report. The summary of key equipment used in technical setup is as under

- **Device-1:** OnePlus Nord CE3 for 3G/2G CAT-15 Smartphone.
- **Device-2:** Samsung Galaxy S23 for 5G/4G/3G/2G CAT-20 Smartphone
- **Drive test Software:** Azenqos Engineering capable Applications to capture actual user experience.

7.1 Appendix-I

7.1.1 Drive test setup

Voice Call		
Call details	Technology	Detail
Call Setup Timeout	• 3G/2G auto mode- switch Call • 5G/4G/3G/2G auto mode- switch Call • 5G/4G MOS Call	30 Sec
Call Duration		120 seconds
Wait/ Guard Time		15 Sec

Table-57: Voice test detail

Note-

- There is 15 sec wait time after locking and before starting first call in 3G/2G call.
- 10 calls to be made at each Hotspot location.
- Minimum 10 Calls to be made during the walk test. Call count will be increased based on walk test distance.
- Speech quality (MOS) has been measured only in city drive & highway by making Mobile to Mobile call.

Data Test		
Test Type	Technology	Detail
HTTP Download	5G/4G/3G/2G Auto Mode	500 MB File- 30 Sec Timeout, (Multithread 3- TCP Connection at a time)
HTTP Upload		250 MB File- 30 Sec Timeout, (Multithread 3- TCP Connection at a time)
YouTube Streaming		20 Sec Video & 25 sec Timeout (Only at Hotspot)
Web Browsing		3 popular websites (www.google.co.in , www.irctc.co.in , sbi.bank.in) 20 sec timeout (only at Hotspot)
Latency & Jitter (TWAMP-UDP)		25 count- Dynamic 500 count- Hotspot Payload- 512 bytes in all drive

Packet Loss Rate (TWAMP-UDP & TCP)		500 counts (TWAMP-UDP) 500 counts (TCP) at each hotspot Payload- 512 bytes in all drive
---------------------------------------	--	---

Table-58: Data test detail

Note-

- 5 Data iteration to be done at each hotspot location.
- Minimum 5 iteration to be made during the walk test. Iteration count will be increased based on walk test distance.
- TWAMP-UDP & TCP test to be performed only once at hotspot location.
- Youtube & Web browsing test to be performed at static location only.
- All values are taken up to two decimal places with round off.
- Delhi-based TRAI server was used for HTTP Download, HTTP Upload, TCP and TWAMP testing for Airtel, BSNL and RJIL.
- VIL server was used for HTTP Download, HTTP Upload, TCP and TWAMP testing, for VIL.




Figure-47: Number of handsets used in city & highway drive

MO: Mobile originating

MT: Mobile terminating




Figure-48: Number of handsets used in railway/metro/walktest/hotspot/coastal area.

Note- 5G & 4G Lock mode testing has been performed at hotspot locations only.

7.1.2 Drive test Methodology

(a) Dynamic voice testing (on the move)




Figure-49: Voice test script for city/railway/metro/highway & coastal area

- 15 sec wait time is applied after locking Radio Access Technology (RAT) to 3G/2G and before starting first call in 3G/2G call.
- Speech quality (MOS) will be measured only City & Highway drive by making Mobile to Mobile calls.

(b) Hotspot voice testing



Figure-50: Voice test script for walktest/hotspot

- 10 calls to be made at each Hotspot location.
- Minimum 10 Calls to be made during the walk test. Call count will be increased based on walk test distance.

(c) Dynamic Data (internet) test




Figure-51: Data test script used in city/metro/railway/highway/walk test & coastal area

(d) Static Data(internet) testing




Figure-52: Data test script used at hotspot

- 5 Data iteration done at each hotspot location
- Min. 5 iteration made during the walk test.
- Web browsing duration mentioned above is for one web site only.
- One ping iteration (with 500 Count of each- TWAMP & TCP) done at hotspot location.

7.2 Appendix-II

7.2.1 Network Performance Parameters for Voice calls

Parameter Name	Definition
Call Setup Success Rate	(i) Call Setup Success Rate is defined as the ratio of Established Calls to Call Attempts. 'Established Calls' mean the following events have happened in call setup: (a) Call attempt is made (b) The signaling channel is allocated (c) The call is routed to the outwards path of the terminating network (d) An alert signal is received by caller in the form of ring back tone, busy tone, or an announcement. CSSR = (Total Call Established/ Total Call Attempt) *100 As per QoS Regulation 2024 benchmark value is >=98%
Drop Call Rate	Call drop represents the service provider network's ability to maintain a call once it has been successfully established. This parameter shall include both incoming calls and outgoing calls which, once they have been established and have an assigned traffic channel/ bearer, are dropped, or interrupted before their normal completion by the user, the cause of the early termination being within the service provider's network Drop Call Rate = (Total Call Drop/Total Call Established) *100 As per QoS Regulation 2024 benchmark value is <=2%
Call Setup Time	Time taken from call initiate to call alerting/ringing. Call Setup Time = T2- T1 T2- Ringing (VoLTE/VoNR) & Alerting (for WCDMA & GSM), T1- Invite (VoLTE/VoNR) & CM Service Request (for WCDMA & GSM)
Voice Quality (MOS)	Voice quality in mobile networks is measured with algorithms based on ITU-T P.863 (POLQA). The grading for Voice quality has been given as: Excellent: MOS ≥ 4 and < 5 Good : MOS ≥ 3 and < 4 Fair : MOS ≥ 2 and < 3 Poor : MOS ≥ 1 and < 2
Handover Success Rate	Handover Success Rate = Count of successful handovers (All Technology Handover combined) / Total count of Handover Attempt (All Technology Handover combined) *100 Handover type which are considered- 2G Inter & Intra cell, 3G Soft & IRAT, 4G Inter & Intra frequency & SRVCC, 5G Inter & Intra frequency & 5G to 4G handovers.
Silence Call	A call which has ≥ 4 sec continuous RTP gap is considered as a Silence Call. Silence call rate = (count of silence call / Total calls established) *100 If a call observes multiple silence count ≥ 4 sec in a particular established call it has been taken as one silent event.

Jitter	The inter arrival jitter is the difference in the relative transit time for two packets. The relative transit time is the difference between a packet's Real-time Transport Protocol (RTP) timestamp and the receiver's clock at the time of arrival, measured in the same units. If S_i is the RTP timestamp from packet i, and R_i is the time of arrival in RTP timestamps units for packet i, then for two packets i and j the inter-arrival jitter D can be expressed as: $D(i,j) = (R_j - R_i) - (S_j - S_i)$ The interarrival jitter is calculated continuously as each data packet i is received from source $SSRC_n$, using this difference D for that packet and the previous packet $i-1$ in order of arrival (not necessarily in sequence), according to the formula $J(i) = J(i-1) + (D(i-1,i) - J(i-1))/16$ or 8																																		
Downlink Packet Drop Rate	Number of RTP (Real-time Transport Protocol) Packets lost divided by total RTP packet received (against each source_SSRC and sequence number) at call originating handset. This KPI is calculated from MOS call for packet call only (VoNR/VoLTE)																																		
Uplink Packet Drop Rate	Number of RTP (Real-time Transport Protocol) Packets lost divided by total RTP packet received (against each source_SSRC and sequence number) at call terminating handset. This KPI is calculated from MOS call for packet call only (VoNR/VoLTE).																																		
Signal Strength	Signal strength is the signal power level received by the wireless user. <table><tr><th rowspan="2">Parameter Name</th><th rowspan="2">Technology</th><th colspan="4">Signal Strength (dBm)</th></tr><tr><th>Excellent</th><th>Good</th><th>Fair</th><th>Poor</th></tr><tr><td>Rx Level</td><td>GSM</td><td>0 to ≥ -65</td><td><-65 to ≥ -75</td><td><-75 to ≥ -85</td><td><-85 to min</td></tr><tr><td>RSCP</td><td>WCDMA</td><td>0 to ≥ -70</td><td><-70 to ≥ -80</td><td><-80 to ≥ -90</td><td><-90 to min</td></tr><tr><td>RSRP</td><td>LTE</td><td>0 to ≥ -80</td><td><-80 to ≥ -95</td><td><-95 to ≥ -110</td><td><-110 to min</td></tr><tr><td>SS_RSRP</td><td>NR</td><td>0 to ≥ -80</td><td><-80 to ≥ -95</td><td><-95 to ≥ -110</td><td><-110 to min</td></tr></table>	Parameter Name	Technology	Signal Strength (dBm)				Excellent	Good	Fair	Poor	Rx Level	GSM	0 to ≥ -65	<-65 to ≥ -75	<-75 to ≥ -85	<-85 to min	RSCP	WCDMA	0 to ≥ -70	<-70 to ≥ -80	<-80 to ≥ -90	<-90 to min	RSRP	LTE	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min	SS_RSRP	NR	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min
Parameter Name	Technology			Signal Strength (dBm)																															
		Excellent	Good	Fair	Poor																														
Rx Level	GSM	0 to ≥ -65	<-65 to ≥ -75	<-75 to ≥ -85	<-85 to min																														
RSCP	WCDMA	0 to ≥ -70	<-70 to ≥ -80	<-80 to ≥ -90	<-90 to min																														
RSRP	LTE	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min																														
SS_RSRP	NR	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min																														

Table-59: Network performance parameter and definition voice

7.2.2 Network Performance Parameters Data tests

Parameter Name	Definition
Download Speed (Mbps)	The download speed is defined as the data transmission rate that is achieved for downloading a test file from a test server to a test device. Download Speed = Total bytes transferred during download / Total time for transfer 80th percentile (upper range) & 20th percentile (lower range) value has been calculated for download throughput in dynamic drive and Hotspot combine data
Upload Speed (Mbps)	The upload speed is the data transmission rate that is achieved for uploading a test file from a test device to a test server. Upload Speed = Total bytes transferred during upload / Total time for transfer. 80th percentile (upper range) & 20th percentile (lower range) value has been calculated for upload throughput in dynamic drive and Hotspot combine data.
Download Session Setup Success Rate	(total download session established (successfully connected to server)/ total download session attempt) *100. This KPI has been calculated for Hotspot only.

Upload Session Setup Success Rate	(total upload session established (successfully connected to server)/ total upload session attempt)*100. This KPI need to report for Hotspot only.
Web Page Download Time	Web browsing test is used to measure performance in terms of opening a web/HTTP page. Time taken to open the web page successfully is considered as web browsing delay/web page download time.
Video Streaming Delay	The Video streaming delay is time taken from start of video transfer to First video frame displayed in player.
Latency (TWAMP-UDP)	Latency is the time it takes for a small data set to be transmitted from a device to a server on the Internet and back to the same device again. The Latency is measured in milliseconds (ms). To calculate the one-way latency, we just do half of the round-trip time. 50th percentile of one-way latency has been reported.
Jitter (TWAMP-UDP)	Measure of variation in time in arrival of packets from a source to destination The consideration of packet delay jitter is considered by standard deviation of Inter Packet Delay Variation. If IPDV is used. By standard deviation is meant the average of standard deviation of IPDV on DL $IPDV(i) = D(i) - D(i-1)$ then Stdvs of IPDV is considered as jitter.
Packet Loss Rate (TWAMP-UDP & TCP)	Number of packets lost out of total packet transferred during test. Packet loss rate = (Total packet lost / Total packet sent) *100 * Packet delay (using TWAMP-UDP & TCP) >90 ms considered as packet loss and included in packet loss rate. * Packet loss rate is calculated based on TWAMP-UDP & TCP. *90th percentile for Packet loss rate has been reported in overall Hotspot performance summary.

Table-60: Network performance parameter and definition Data

Disclaimer: The observations presented above and, in the reports, represent the performance of the service providers on the area/route under test on the day/time of conducting the drive test and no inference whatsoever may be drawn regarding the quality of the telecom service by the service providers in the whole city/state/licensed service area.